

Sustainable design of sanitation system based on material and value flow analysis for urban slum in Indonesia

著者別名	入江 光輝
journal or publication title	Frontiers of Environmental Science & Engineering
volume	7
number	1
page range	120-126
year	2013-02
権利	(C) Higher Education Press and Springer-Verlag Berlin Heidelberg 2012. The original publication is available at www.springerlink.com .
URL	http://hdl.handle.net/2241/118618

doi: 10.1007/s11783-012-0460-5

6 Sustainable design of sanitation system based on material and 7 value flow analysis for urban slum in Indonesia

8 Ken USHIJIMA (✉)¹, Mitsuteru IRIE², Neni SINTAWARDANI³, Jovita TRIASTUTI³, Umi
9 HAMIDAH³, Tadaharu ISHIKAWA⁴, Naoyuki FUNAMIZU¹

10 ¹ Environmental Engineering and Science, Hokkaido University, Sapporo-shi, Hokkaido 060-8628, Japan

11 ² Alliance for Research on North Africa, University of Tsukuba, Tsukuba City, Ibaraki 305-8572, Japan

12 ³ Research Centre for Physics, Indonesian Institute of Sciences, Bandung 40135, Indonesia

13 ⁴ Department of Environment and Technology, Tokyo Institute of Technology, Yokohama 226-8502,
14 Japan

15

16 © Higher Education Press and Springer-Verlag Berlin Heidelberg 2012

17

18 **Abstract** Material flow analysis (MFA) and value flow analysis (VFA) were applied to the sanitation
19 system in an urban slum in Indonesia. Based on the results of the MFA and VFA, garbage and excreta
20 disposal costs were evaluated to be 0.7% and 1.1%, respectively, of per capita income. Such value flows
21 seem reasonable in light of the recognized affordability to pay (ATP) standard. However, current excreta
22 disposal methods create negative impacts on downstream populations. Because such disadvantages do not
23 go back to disposers, but passed to downstream, the current value flow structure does not motivate
24 individual toilet users to install treatment facility. . Based on current material and value flow structures, a
25 resource recycling sanitation system scenario was examined. Based on VFA, an affordable initial cost for
26 such a system was calculated; this was found to be comparable in price to a cheaper composting toilet that
27 is currently available in the market.

28

29 **Keywords** material flow, value flow, resource recycling system, sustainable design, initial cost, urban
30 slum

31

32

33 1 Introduction

34

35 Highly populated urban areas require large material inflows of food for people. Although this incoming
36 materials is consumed, it does not disappears, because waste materials is generated, which needs to be

1 disposed of in some manner, mainly as solid waste and as waste water, including toilet waste water. If the
2 urban system does not introduce systems to manage these material outflows, unfavorable wastes
3 accumulate in the urban area or flow to unfavorable locations, such as into surface and ground water
4 reservoirs, both of which are usually important water sources. Such problems can be observed in many
5 developing countries [1–3], and although it is recognized that solutions to such problems are needed,
6 investment in outflow systems tends to be given lower priority because they do not have clear direct
7 benefits, unlike projects such as production, supply, and transportation.

8 On the other hand, sustainability has recently been recognized as important factor for societies system.
9 Several types of resource recycling toilets and wastewater treatment systems for reuse have been proposed
10 as sustainable sanitation system technologies [4–6]. Although these technologies have the advantage, that
11 they can create value from unwanted waste, they need to be embedded in system designed suitably to
12 manage equipment outflow. It is therefore important to understand current and future material flows in and
13 around targeted urban areas. Material flow analysis (MFA) or substance flow analysis (SFA) are suitable
14 methodologies for this purpose. The application of the MFA to sanitation systems has been attempted in
15 several studies, some of which considered sanitation systems as a part of material flows [7,8], and some of
16 which focused mainly on sanitation system [9,10]. However these studies describe current material flows
17 and only providing the conceptual description of possible improvements.

18 In an actual application, the optimization of the material flow design is not sufficient to drive the system.
19 Successful material flow programs needs to be designed such that they benefit all stakeholders and
20 incorporate well planned value chains. Therefore, it is believed that both material flow and value flow
21 should be considered simultaneously. In this study, material flow is attempted to be related with value flow
22 for designing sustainable sanitation systems for a slum area in Bandung, Indonesia, which have been
23 studied comprehensively.

26 2 Materials and methods


28 2.1 Overview of study site

29
30 Bandung is the fourth largest city in Indonesia, with a population of 2.5 million [11]. It is in the inland part
31 of west Java and is located upstream of the Citarum River, a major source of water for the capital, Jakarta
32 (Fig. 1(a)). Only 16% of the domestic wastewater generated in Bandung City is treated, as the city has only
33 one treatment plant, located in the suburbs [12]. The Kiaracandong sub-district is located near the center of
34 Bandung city, and is known as the city's largest slum. According to 2006 local statistics, Kiaracandong has
35 a population of 116000 living within an area of 6.1 km².

36 Two types of field surveys were conducted. One was conducted in the Jondol Canal [13], which flows
37 through central Kiaracandong into the Cicadas River, which is a tributary of the Citarum River. In the area
38 surveyed, there were no houses connected to the sewerage system feeding the treatment plant. Figure 1(c)

1 shows the measurement locations and catchment of the studied section of the Jondol Canal, with a distance
2 of 960 m between the two observation sites. This area of the catchment was measured to be 0.41 km² and,
3 as determined by previous investigations and local statistics, has a population of 16240 people and 3585
4 households. The other survey was conducted in the Jondol Canal catchment area. In this survey, sixty-two
5 families living near the canal were interviewed about their water use, their wastewater disposal, and other
6 related matters [13].

7



8

9 **Fig. 1** Location of studied area: (a) location of Bandung City; (b) Kiaracandong Sub District; (c) observatories and
10 catchment

11

12 2.2 Data sources

13

14 The results of field surveys on river water [13], domestic wastewater [13,14], and garbage disposal and
15 collection [15], in addition to official statistics for Indonesia [16], were used as the main data.

16

1 2.3 Methods

2

3 MFA and SFA were used to analyze current and future sanitation systems from a comprehensive and
 4 practical viewpoint. The subjects covered in the MFA included excrement as well as all related materials,
 5 namely, water and food. The SFA was conducted along a similar framework, focusing on nitrogen and
 6 phosphorus which, as major components of fertilizers, are important factors in resource recycling systems.
 7 When data for the slum area were unavailable, data from statistics and literature on Indonesia or other
 8 South-east Asian countries were used for extrapolation. The project boundary was set as the catchment
 9 area described in Fig. 1(c). All the data were expressed in terms of per capita years, because both material
 10 and value flows are discussed together in this study and the use of such unit is meaningful to the study of
 11 value flow.

12 MFA and SFA were also used for estimating value flow. In contrast to material and substance flows,
 13 value flow can be measured in a number of ways. Some can be definitely measured in quantitative factors
 14 such as prices or monetary value, whereas some can be only evaluated in qualitative factors, such as status
 15 or comfort derived. In this study, the quantitative values were evaluated based on the available data,
 16 whereas qualitative values were simply determined to be positive or negative by assessing the directions of
 17 material and value flows.

18 Material, substance, and value flow analysis were conducted for two scenarios: one representing current
 19 conditions, and the other assuming the implementation of a resource recycling sanitation system involving
 20 the installation of a urine diversion aerobic composting toilet [17] in each household. The framework
 21 proposed and discussed quantitatively by Ushijima [14] for the collection of urine and compost for
 22 integration with existing garbage collection systems, wherein organic solid waste is processed in a
 23 composting toilet along with feces, was applied.

24 Successful diffusion of this resource recycling system primarily depends on each household's decision
 25 of whether to install the composting toilet. This decision is based on the following criterion:

$$26 \quad (\text{Initial cost} / \text{expected lifetime}) < (\text{WTP for excreta disposal}) + (\text{income from selling excreta}), \quad (1)$$

27 where WTP is "willingness to pay". Here, *WTP for excreta disposal* is estimated by

$$28 \quad (\text{WTP for excreta disposal}) = (\text{Current excreta disposal cost}) + (\text{Initial cost for water flush toilet} / \text{expected} \\ 29 \quad \quad \quad \text{lifetime}), \quad (2)$$

30 where the *Current excreta disposal cost* is equal to the sum O_c11+O_c12 , given in Table 1

31

32 **Table 1** Mass, Phosphorus, Nitrogen and value of each arrow in current material flow

ID	supplied item	mass /(kg·(year·capita) ⁻¹)	P	N	value /(Rp·(year·capita) ⁻¹) /(% against income)	data source
I _c 1	water	32000	0	0	+ 110000 (2.8%)	mass, value: average of 3 households in Ushijima[14]. P, N: regarded as ignoreable

I _{c2}	food	170	1.3	6.0	+ 1400000 (35.9%)	mass, value: Gunawan[16], P, N: blackwater + solid waste
I _{c3}	electricity	0	0	0	+ 170000 (4.4%)	value: average of 3 households in Ushijima[14], mass, P, N: meaningless
O _{c1}	blackwater	14000	1.2	5.9	± 0 (0%)	mass: I _{c1} ×0.41[14] + O _{c11} + O _{c12} , P, N: O _{c11} + O _{c12} mass, P, N: Ushijima[14],
O _{c11}	feces	33	0.3	0.9	-13000 (0.3%)	value: water consumption for defecation (water cost × percentage of water use for defecation) mass, P, N: Ushijima[14],
O _{c12}	urine	370	0.9	5.0	-32000 (0.8%)	value: water consumption for urination (water cost × percentage of water use for urination) mass: I _{c1} -O _{c1} , P, N: total wastewater (maximum in Ushijima [14]) - O _{c1} mass: Ushijima [14],
O _{c2}	graywater	19000	1.0	0.0	± 0 (0%)	P, N: total wastewater (maximum in Ushijima [14]) - O _{c1} mass: Ushijima [14],
O _{c3}	solid waste	67	0.1	0.2	-28000 (0.7%)	P, N (unit): Aramaki & Thuy [8], value: collection fee (Ushijima [14])
O _{c31}	junk material	(no data)	0	0	+	P, N: non-organic is regarded as 0
O _{c32}	solid waste	(no data)	0.1	0.2	-	D3-D31
O _{c33}	junk material	(no data)	0	0	+	P, N: non-organic is regarded as 0
O _{c34}	accumulation	(no data)	0.1	0.2	-	D32-D33 mass, P, N: meaningless
O _{c4}	work force	0	0	0	+ 3900000 (100%)	value: average of 3 households in Ushijima[14] Ushijima[14],
R _{c1}	river inflow	52000	0.4	1.3	± 0 (0%)	N: NH ₄ -N + NO ₂ -N + NO ₃ -N P: PO ₄ -P Ushijima[14],
R _{c2}	river outflow	110000	1.2	3.5	± 0 (0%)	N: NH ₄ -N + NO ₂ -N + NO ₃ -N P: PO ₄ -P Ushijima[14]
R _{c3}	mosque	8300	0	0	± 0 (0%)	Ushijima[14]

1

2

3 3 Results


4

1 3.1 Current material flow

2

3 **Figure 2** shows current material flows. Total mass flow, phosphorus mass flow, nitrogen mass flow, and
 4 total value flows are summarized in **Table 1**. Note that several value flows, namely, I_{c21} , I_{c22} , I_{c23} , I_{c24}
 5 and I_{c25} were not quantified in this study.

6



7

8 **Fig. 2** Current material flow

9


10 3.2 Material flow of resource recycling sanitation system

11

12 **Figure 3** shows material flows under a future scenario in which a resource recycling sanitation system is
 13 applied. Total mass flow, phosphorus mass flow, nitrogen mass flow, and total value flows are summarized
 14 in **Table 2**. Note that several mass flows, namely, I_{r21} , I_{r22} , I_{r23} , I_{r24} , and I_{r25} were not quantified in this
 15 study.

16

1



2

3 **Fig. 3** Material flow of resource recycling scenario

4

5 **Table 2** Mass, phosphorus, nitrogen and value of each arrow in material flow of resource recycling sanitation system.

ID	supplied item	mass/ (kg·(year·capita) ⁻¹)	P/ (kg·(year·capita) ⁻¹)	N/ (kg·(year·capita) ⁻¹)	value/ (Rp·(year·capita) ⁻¹) (% against income)	data source
I _r 1	water	32000	0	0	+ 110000 (2.8%)	mass, value: average of 3 households in Ushijima[14]. P, N: regarded as ignorable
I _r 2	food	170	1.3	6.0	+ 1400000 (35.9%)	mass, value: Gunawan[16], P, N: blackwater + solid waste
I _r 3	electricity	0	0	0	+ 170000 (4.4%)	value: average of 3 households in Ushijima[14], mass, P, N: meaningless
O _r 11	feces	33	0.3	0.9	variable	mass, P, N: Ushijima[14], value: water consumption for defecation (water cost × percentage of water use for defecation)
O _r 12	urine	370	0.9	5.0	variable	mass, P, N: Ushijima[14], value: water consumption for urination (water cost × percentage of water use for urination)
O _r 13	processed feces	variable	0.3	< 0.9	variable	P, N: = O _r 11

O _r 14	processed urine	variable	0.9	< 5.0	variable	P, N: = O _r 12
O _r 15	collected feces	variable	0.3	< 0.9	variable	P, N: = O _r 11
O _r 16	collected urine	variable	0.9	< 0.9	variable	P, N: = O _r 12
O _r 2	graywater	19000	1.0	0.0	± 0 (0%)	mass: I _c 1-O _c 1, P, N: total wastewater (maximum in Ushijima [14]) - O _c 1
O _r 3	solid waste	17	0.0	0.0	-28000 (0.7%)	mass: Ushijima[14], P, N: non-organic is regarded as 0, value: collection fee (Ushijima[14])
O _r 31	junk material	(no data)	0	0	+	P, N: non-organic is regarded as 0
O _r 32	solid waste	(no data)	0.0	0.0	-	D3-D31
O _r 33	junk material	(no data)	0	0	+	P, N: non-organic is regarded as 0
O _r 34	accumulation	(no data)	0.0	0.0	-	D32-D33
O _r 35	organic waste	50	0.1	0.1	+	mass: Ushijima [14], P, N (unit): Aramaki & Thuy [8]
O _r 4	work force	0	0	0	+ 3900000 (100%)	mass, P, N: meaningless, value: average of 3 households in Ushijima [14]
R _r 1	river inflow	52000	0.4	1.3	± 0 (0%)	Ushijima[14], N: NH ₄ -N + NO ₃ -N P: PO ₄ -P
R _r 2	river outflow	97000	0.8	3.5	± 0 (0%)	Ushijima[14], N: NH ₄ -N + NO ₃ -N P: PO ₄ -P, reaching ratio of N, P: 0.36
R _r 3	mosque	8300	0	0	± 0 (0%)	Ushijima[14]

1

2

3 4 Discussion

4

5 4.1 Current material flow

6

7 Using material flow and value flow analysis, the value flow in and around an urban slum family were
8 analyzed, not only in terms of easy-to-price factors or quantitative flows but also in terms of
9 difficult-to-price factors or qualitative flows, such as garbage disposal and excreta disposal. Based on the
10 result, “costs for disposal” for garbage and wastewater were determined. These values, listed in Table 1 are
11 approximately 0.7% and 1.1% of per capita income for garbage disposal and for urine and excreta disposal,
12 respectively. The World Bank has roughly evaluated benchmarks for affordability to pay (ATP) as 2% and
13 1% of consumable per capita income for garbage collection service and sewerage service, respectively [18],
14 similar to the current costs derived here. Thus, current value flows for garbage and excreta disposal seem
15 reasonable for people in light of such benchmarks. However, the material flow of excreta into the river is
16 clearly causing deterioration of the water environment. Because this value loss has a negligible direct

1 effect, and because the disadvantages apply to populations downstream instead of to disposers, it would
2 seem that the structure of the current value flow would impede efforts to improve the water environment.

4 4.2 Resource recycling system

6 A proposed resource recycling sanitation system would not discharge excreta to the river; rather such
7 waste would be sent to farms, where it would have positive value as a fertilizer. From the catchment area
8 studied, the system would remove almost all the nitrogen and half of the phosphorus discharged, and
9 therefore, the net flux of nitrogen and phosphorus through the river under a recycling scenario (see Fig.3:
10 R_r2-R_r1) would be less than under current conditions (Fig.2: R_c2-R_c1). The positive impacts on river water
11 quality resulting from the introduction of resource recycling sanitation would be potentially large.

12 As it is a source of nutrients, excreta has good potential for the generation of value through use as
13 fertilizer. However, the value of compost made from human excreta may also be discounted relative to
14 chemical fertilizers because of psychological resistance. Further, the quality or handling of the processed
15 excreta may also affect the value of the resulting compost. However, the price of synthetic fertilizers has
16 been rising the last decade, and if this rise continues, the incentive of saving costs through substitution may
17 overcome the psychological barriers.

18 In any event, the exact value of human excreta is currently difficult to evaluate. A case study of one
19 company selling liquid fertilizer made from human urine seems suitable as a reference [19]. The company
20 pays 1000 Rupiah·L⁻¹ to people as compensation for urine offer. Assuming that one liter of urine is
21 produced per capita per day, this price corresponds to 365000 Rupiah·(capita·year)⁻¹, equivalent to 9% of
22 per capita income, which is listed in Table 1 as O_c4.

23 In the area studied, the initial cost of a water flush toilet is reported to be approximately 2000000 Rupiah
24 [14]. Assuming a family size of four people and a toilet lifetime of 15 years (which is standard in Japan),
25 the WTP is thus estimated at 79000 Rupiah·(capita·year)⁻¹. If we apply the excreta price mentioned above
26 as an optimum estimation, affordable initial cost for resource recycling sanitation system is estimated as

$$(Initial\ cost / lifetime) < 4400000\ Rupiah \cdot (capita \cdot year)^{-1}, \quad (3)$$

28 For a 15-year lifetime composting toilet, the estimated affordable initial cost for a four person family
29 would be 27000000 Rupiah, equivalent to approximately 3200 USD according to the June 2011 exchange
30 rate. This is similar in price to a cheaper composting toilet (approximately 2000 USD) currently available
31 in the market.

34 5 Conclusions

36 In this study, for an urban slum, the material and value flows of water, sanitation related materials,
37 nitrogen, and phosphorus were calculated and plotted. The value flow analysis evaluated garbage disposal

1 cost and excreta disposal cost at 0.7% and 1.1%, respectively, of household income, which represents a
2 reasonable cost to disposers. However, under the current disposal scheme, negative value due to excreta
3 disposal appears to be passed on to downstream populations. The structure of this value flow suggests that
4 little attention is paid to the negative externalities, indicating that a solution in this case may be difficult to
5 obtain.

6 The affordable initial cost of a new resource recycling system was evaluated and compared with the
7 costs of a currently used commercial compost toilet by evaluating equipment lifetimes and potential
8 income streams available from the sale of human excrement fertilizers. To estimate a value for the human
9 excrement fertilizer, real-world case study in Indonesia, in which money was paid in exchange for human
10 urine, was referred to. The evaluated affordable initial cost derived was sufficiently comparable to the
11 price of a cheaper composting toilet currently available in the market. This implies that such a resource
12 recycling system is feasible even in an urban slum.

13
14
15 **Acknowledgements** This research was financially supported by the Core Research for Evolutional
16 Science and Technology of the Japan Science and Technology Agency (JST-CREST), the Science and
17 Technology Research Partnership for Sustainable Development of the Japan Science and Technology
18 Agency and Japan International Cooperation Agency (JST-JICA-SATREPS), and the science research S of
19 the Grants-in-Aid for Scientific Research of Japan Society for the Promotion of Science.

22 **References**

- 24 1. Metcalf & Eddy International Inc. in association with Brockman Tym International and TCGI
25 Engineers. Pasig River Development Plan, Final Report to ADB, vol.1. Quezon City: Metcalf & Eddy International Inc. in
26 association with Brockman Tym International and TCGI Engineers, 1998
- 27 2. Tanaka N. Environment of developing countries in Asia-Pacific, Thai (1). Journal of Resources and
28 Environment, 1992, 28(11): 1065–1076 (in Japanese)
- 29 3. Tsuzuki Y, Koottatep T, Rahman M D M, Ahmed F. Preliminary study on pollutant discharge from
30 domestic wastewater and pollutant load in the river: a comparative study between Japan, Thailand and
31 Bangladesh. In: Proceedings of the Water Environment Partnership in Asia (WEPA) Forum on "Water Environmental
32 Governance in Asia", Bangkok. Kanagawa: Water Environment Partnership in Asia (WEPA), 2007
- 33 4. Winblad U, Simpson-Hebert M. Ecological Sanitation – Revised and Enlarged Edition. Stockholm: SEI, 2004
- 34 5. Lopez Zavala M A, Funamizu N, Takakuwa T. Onsite wastewater differentiable treatment system:
35 modeling approach. Water Science and Technology, 2002, 46(6–7): 317–324
- 36 6. Ushijima K, Ito K, Ito R, Funamizu N. Greywater treatment by slanted soil system. Ecological Engineering
37 2012papers in press, doi: 10.1016/j.ecoleng.2012.04.028

- 1 7. Harada H, Adachi T, Fujii S, Lien N P H, Hai H T. Phosphorus flow analysis in Hanoi focusing on
2 wastewater, agriculture and stockbreeding. *Environmental Engineering Research, JSCE*, 2010, 47: 465–474
3 (in Japanese)
- 4 8. Aramaki T, Thuy N T T. Material flow analysis of nitrogen and phosphorus for regional nutrient
5 management: case study in Haiphong, Vietnam. *Sustainability in Food and Water. Alliance for Global
6 Sustainability Bookseries*, 2010, 18(6): 391–399 [doi:10.1007/978-90-481-9914-3_38](https://doi.org/10.1007/978-90-481-9914-3_38)
- 7 9. Zhou C, Liu J, Wang R, Yang W, Jin J. Ecological-economic assessment of ecological sanitation
8 development in the cities of Chinese Loess Plateau. *Ecological Complexity*, 2010, 7(2): 162–169
9 [doi:10.1016/j.ecocom.2009.10.001](https://doi.org/10.1016/j.ecocom.2009.10.001)
- 10 10. Li S, Yuan Z, Bi J, Wu H. Anthropogenic phosphorus flow analysis of Hefei City, China. *The Science
11 of the Total Environment*, 2010, 408(23): 5715–5722 [doi:10.1016/j.scitotenv.2010.08.052](https://doi.org/10.1016/j.scitotenv.2010.08.052) PMID:20863550
- 12 11. Statistics Indonesia B P S. *Seri Kependudukan Jawa Barat Tahun 1920–2005*. Jakarta: BPS, Indonesia, 2005
- 13 12. World Bank. *Indonesia Environment Monitor 2003*. Jakarta: World Bank Indonesia Office, 2003
- 14 13. Ushijima K, Irie M, Sintawardani N, Triastuti J, Ishikawa T. Field research on domestic wastewater
15 from a slum in Bandung City. *Journal of Hydrosience and Hydraulic Engineering*, 2008, 26(1): 129–140
- 16 14. Ushijima K. Study on water environment rehabilitation by introducing new toilet system in urban area of Southeast Asia.
17 Dissertation for the Doctoral Degree. Tokyo: Tokyo Institute of Technology, 2007 (in Japanese)
- 18 15. Ushijima K, Irie M, Sintawardani N, Triastuti J, Ishikawa T. Practical model design of sustainable sanitation
19 system in urban slum. In: *Proceedings of the 6th International Symposium on Sustainable Sanitation, Changchun*. Changchun:
20 Northeast Normal University (NENU), 2008, 27–33
- 21 16. Memed Gunawan. *Market Prospects for Upland Crops in Indonesia, the CGPRT Centre Working Paper Series 25*. Bogor:
22 Regional Co-ordination Centre for Research and Development of Coarse Grains, Pulses, Roots and Tuber Crops in the Humid
23 Tropics of Asia and the Pacific (CGPRT), 1997
- 24 17. Ushijima K, Yabui K, Hijikata N, Ito R, Funamizu N. Development of self-buildable simple composting toilet. In:
25 *Proceedings of IWA ASPIRE, Tokyo*. Tokyo: the 4th IWA-ASPIRE Organizing Committee, 2011
- 26 18. Japan International Cooperation Agency (JICA). *Study on Method of Economic Evaluation in Development Studies*.
27 Tokyo: JICA, 2002 (in Japanese)
- 28 19. Ushijima K, Irie M, Sintawardani N, Triastuti J, Ishikawa T, Funamizu N. Sanitation model for urban slum in
29 Southeast Asia. In: *Proceedings of IWA 2nd Development Congress, Kuala Lumpur, Malaysia*. London: IWA, 2011