

**Master's Thesis in Graduate School of
Library, Information and Media Studies**

**Maintaining and Publishing Metadata
Application Profiles with Extensible
Authoring Format**

September 2019

201726107

Nishad Thalhath Rehumath

Maintaining and Publishing Metadata Application Profiles with Extensible Authoring Format

Nishad Thalhath Rehumath

**Graduate School of Library,
Information and Media Studies
University of Tsukuba**

September 2019

Maintaining and Publishing Metadata Application Profiles with Extensible Authoring Format

Student No.: 201726107
Name: Nishad Thalhath Rehumath

Metadata Application Profiles are the elementary blueprints of any Metadata Instance. They act as a key element in metadata interoperability. Singapore Framework for Dublin Core Application Profiles defined the framework for designing metadata application profiles to ensure interoperability and reusability.

There are various accepted formats to express application profiles. Most of these expression formats such as RDF, OWL, JSON-LD, SHACL, and ShEx are machine actionable, and formats like spreadsheets or web pages act as human-readable documentation. Due to limited options in the mutual conversion of these expression formats, they are often created independent of each other and thus makes the process expensive requiring sophisticated skills and time. Proposals for convertible authoring formats to create application profiles have received less acceptance, mainly due to their inability to address various use cases and requirements.

As a result, domain experts find it difficult to create application profiles, considering the technical aspects, costs and disproportionate incentives and the lack of easy-to-use tools for Metadata Application Profile creation.

This study proposes Yet Another Metadata Application Profile (YAMA) as a user-friendly authoring format for creating, maintaining and publishing Metadata Application Profiles. YAMA helps to produce various standard expressions of the Metadata Application Profiles, change logs, and different versions, with an expectation of simplifying Metadata Application Profile creation process for domain experts. YAMA includes an integrated syntax for recording application profiles as well as changes between different versions. A proof of concept toolkit, demonstrating the capabilities of YAMA is also being developed. YAMA boasts a human readable yet machine actionable syntax and format, which is seamlessly adaptable to modern version control workflows and expandable for any specific requirements.

This study argues that the extensible authoring formats are suitable for creating application profiles with custom requirements and different use cases. This would promote the acceptance of application profiles by reducing the associated cost and skill requirements in creation, maintenance, and publishing of application profiles.

Academic Advisors: Principal: SAKAGUCHI Tetsuo
Secondary: NAGAMORI Mitsuharu

Contents

1	Introduction	1
1.1	Metadata Application Profiles	1
1.2	The Singapore Framework for Dublin Core Application Profiles	1
1.3	Management of Application Profiles	3
2	Status of Application Profile	4
2.1	Various Attempts in the Last Decade	4
2.2	Current Status and Availability of Application Profiles	4
2.3	Expression Formats for Application Profiles	5
2.4	Authoring Formats for Application Profiles	5
3	Problems and Challenges in MAP Authoring	7
3.1	Challenges in Metadata Application Profile Creation	7
3.2	MAP creation for various domains	7
3.3	Limitation of existing Authoring formats	8
3.4	Provenance and Change logs	8
4	Proposed Solutions	9
4.1	Interoperable Formats	9
4.2	Change logs and Roadmaps	9
4.3	Tooling	10
4.4	Extendable Authoring Formats	10
5	YAMA: Yet Another Metadata Application Profile	11
5.1	YAMA as an Authoring Format	12
5.2	YAML as a Promising Format	12
5.3	Extensibility of YAMA	13
5.4	Expected outputs for YAMA	14
5.5	Possible use-cases for YAMA	14
5.6	Advantages of YAMA as an authoring format	15

6 YAMA Syntax and Specifications	17
6.1 Expressing Application Profiles in YAMA	17
6.2 Changesets in YAMA	20
6.3 YAMA Use Cases and Aims	20
6.4 Integrating, Extending and Maintaining YAMA	21
6.5 Recommendations and Best Practices	22
7 YAMA Toolkit	23
7.1 Python module & Command Line Interface	23
7.2 Templates and generators	24
8 Related Works	26
8.1 DCMI Description Set Profiles	26
8.2 Metabridge Simple DSP (SDSP)	27
8.3 Me4DCAP	27
8.4 IMI Data Model Description (DMD)	28
8.5 Bibframe Profile Editor	28
9 Comparison & Evaluation	30
9.1 Results	31
9.2 Versioning, Changelogs and Provenance	35
10 Discussion	36
10.1 Continuation and future plans	37
11 Conclusion	38
Acknowledgement	39
References	40
Appendices	42

List of Figures

1.1	A general overview of a Metadata Application Profile	2
1.2	Singapore Framework for Dublin Core Application Profiles	3
2.1	Authoring formats and expression formats for application profiles .	6
5.1	Extensibility of a YAMA Application Profile	13
5.2	Components of YAMA and their expected outputs	16
6.1	Structure of YAMA Document	18
6.2	An example of a YAMA document	19
6.3	Structure of YAMA ChangeSets	20
6.4	Example of YAMA ChangeSet	21
7.1	A basic Jinja template example	25
8.1	Basic structure of DC Description Set Profiles, a constraint language for Dublin Core Application Profiles	27
8.2	Package structure of DMD (Translated)	29
8.3	DCAT-AP in BIBFRAME Profile Editor	29
9.1	Classes from DCAT-AP shows extensibility of YAMA	32

List of Tables

2.1	Attempts on application profile creation	4
9.1	Feature comparison of three authoring formats used for evaluation.	31
9.2	Comparison of general use cases for application profile authoring formats.	33
9.3	Comparison of use cases for extensible MAP authoring formats. . .	34
9.4	Support for provenance description	35

Chapter 1

Introduction

1.1 Metadata Application Profiles

The concept of Metadata Application Profiles (MAP) or simply Application Profiles (AP) is not new in the information science community. The initial definition of application profiles is “schemas, which consist of data elements drawn from one or more namespaces, combined together by implementers, and optimized for a particular local application.” [7]

A MAP is the elementary blueprint of a metadata instance. It describes the set of metadata elements, policies, guidelines, and vocabularies defined for a particular domain, or implementation. It also declares the metadata terms, information resource, application, or uses. A well-defined application profile documents schemes, vocabularies, policies, and required elements, etc. [1, 9]. Application profiles for metadata instances play a crucial role to provide the authoritative specification of term usage, support, and document the evolution of vocabularies, facilitate interoperability by informing domain consensus, encourage alignment of practice, enable interpretation of legacy metadata and explain the structure of data to data consumers [1, 7, 9]. A general overview of a MAP is given in figure 1.1.

1.2 The Singapore Framework for Dublin Core Application Profiles

The Singapore Framework for Dublin Core Application Profiles ¹ is a framework proposed for designing metadata applications. Singapore Framework ensures maximum interoperability and reusability by documenting applications. This framework specifies a set of descriptive components necessary for documenting an application profile and describing the relationship between these documented standards domain models and semantic web standards. This framework establishes a basic guideline for evaluating application profiles for completeness of documentation

¹<http://dublincore.org/specifications/dublin-core/singapore-framework/>




Figure 1.1: A general overview of a Metadata Application Profile

and confirms with the principles of web-architecture [5]. Singapore Framework is illustrated in figure 1.2.

Singapore Framework defines a Dublin Core Application Profile as a packet of documentation which consists of different components. They are :

1. Functional requirements, which describe the functions that the application profile supports. Also acts as a basis of evaluating the application profile for internal consistency and gives guidance on the aptness of the application profile for a specific use.
2. Domain model, which defines the basic entities described by the application profile and their primary relationships. Domain model defines a necessary scope for the application profile.
3. Description Set Profile (DSP), which is a set of metadata records that are valid instances of an application profile. The Dublin Core Description Set Profile (DSP) offers a simple constraint language based on the DCMI Abstract Model.
4. Usage guidelines, which describe the application of the application profile
5. Encoding syntax guidelines describe any application profile-specific syntaxes and syntax guidelines.

Singapore Framework also includes the other two components, Domain Standards, and Foundation Standards.




Figure 1.2: Singapore Framework for Dublin Core Application Profiles

1.3 Management of Application Profiles

Metadata application profile management can be separated into three distinct stages. The first and the critical stage is planning and designing of an application profile. In which domain experts design a domain-specific metadata application profile by selecting vocabularies from different namespaces and combining them to make it suitable for a specific local application. The next stage is creating and publishing of this application profile, which involves creating human-readable documentation and machine-actionable expressions of the application profile. This stage is more technical than planning and designing. The third and final stage is updating and maintaining application profiles. This third stage is a continuous process which includes updating the versions of the application profiles along with its development and maintaining changelings as well as ensuring the availability of current and previous versions of the application profiles and different expression formats.

Chapter 2

Status of Application Profile

2.1 Various Attempts in the Last Decade

Even though the idea of mixing and matching metadata elements was proposed in 2000, a complete recommendation was presented by DCMI in 2004 as DCMI abstract model of MAP [20]. In 2007, DCMI presented the Singapore Framework for Dublin Core Application Profiles as a framework for designing metadata applications for interoperability and for documenting for reusability [17]. As a centerpiece of Singapore Framework, DCMI proposed DSP, a constraint language for Dublin Core application profiles [17]. In 2009, Guidelines for Dublin Core Application Profiles published and as a translator for DC DSP, MoinMoin Wiki Syntax for DSP to integrate application profiles in webpages and wikis was introduced [5]. Other than DCMI, MetaBridge project introduced a spreadsheet-based application profile format named Simple DSP (SDSP) in 2011 [15]. The recent development was an ongoing initiative by Karen Coyle, known as RDF-AP, which at the moment utilizes CSV-based notations to create application profiles which are supposed to be machine-actionable as well. [4].

2.2 Current Status and Availability of Application Profiles

The availability, maintenance, and distribution of application profiles are not standardized. Identifying MAPs requires human involvement [14]. Curating and

Table 2.1: Attempts on application profile creation

Year	Initiative
2004	DCMI Abstract Model DCMI Recommendation [20]
2007	Singapore Framework for Dublin Core Application Profiles [17]
2008	DCMI DC-DSP [16]
2009	A MoinMoin Wiki Syntax for DSP [5]
2011	MetaBridge Simple DSP [15]
2017	RDF-AP [4]

archiving MAPs are challenging and expensive due to this manual effort involved. Various registry projects still depend on manual contributions than automated approaches. Publication of application profiles is only in human-friendly formats, which requires human involvement in the identification processes to distinguish them from other documents. Extracting structured application profile information from spreadsheets or PDF documents is difficult. Lack of versioning, changelogs, and previous versions strongly affect the longevity and provenance of metadata information. Absence of standardized publication formats restricts automated harvesting of application profiles, which eventually limits the number of available application profiles in various registry attempts. Metadata registries were intended to use application profiles to promote and support interoperability and reuse [15]. Also, there is a lack of a standardized way to associate data with the MAP on which it is based [23] [24].

2.3 Expression Formats for Application Profiles

MAP publication consists of both human-friendly and machine-actionable format. The human-friendly format includes documentation of MAP in HTML, Spreadsheet, PDF, and DOCX. Standard machine-friendly expression formats are RDF¹, OWL², and JSON-LD³. Validation formats like Shapes Constraint Language (SHACL)⁴ and Shape Expressions (ShEx)⁵ will not only help to validate the data but they are capable of expressing entire application profile actionable as well. Due to limited options in the mutual conversion of these expression formats, they are often created independent of each other and thus makes the process expensive by demanding sophisticated skills and time.

Detailed class diagrams, as well as documentation in different formats, will make the application profiles cover more use-cases. In general, a well-defined metadata application profile requires different expression formats to make it cover the maximum recommendations from the Singapore Framework for Dublin Core Application Profiles [17].

2.4 Authoring Formats for Application Profiles

An authoring format of application profile can be defined as a source for application profile publication, which helps to generate different application profile expression formats using a processor or converter. Authoring formats cannot be treated as an

¹<https://www.w3.org/RDF/>

²<https://www.w3.org/OWL/>

³<https://json-ld.org/>

⁴<https://www.w3.org/TR/shacl/>

⁵<http://shex.io/>




Figure 2.1: Authoring formats and expression formats for application profiles

expression of an application profile, as they may not be a standard representation of an application profile, and their capability to do so always depends on its processors or designated tools. This clear separation between authoring and expression formats is illustrated in Figure 2.1.

There were different attempts to define and develop authoring formats or tools in application profile creation. The first notable attempt is by DCMI, along with DCMI's proposal for DSP as a constraint language for Dublin Core application profiles, introduced a translator which used MoinMoin Wiki Syntax as an authoring format for DSP to integrate application profiles in webpages and wikis was introduced [5]. MetaBridge project introduced a spreadsheet-based application profile authoring format named Simple DSP (SDSP) [15]. One of the recent developments is an ongoing initiative named RDF-AP, which at the moment utilizes CSV-based notations to author application profiles [4]. The BIBFRAME project from the Library of Congress has developed two web-based profile editors named BIBFRAME Profile Editor, which allows to modify or create profiles [3]. BIBFRAME editor is mainly intended to create the profiles of the BIBFRAME vocabulary but can be usable for other profiles as well. Linked Data for Production 2 (LD4P2) project published a modified BIBFRAME editor as a general online application profile authoring tool named Sinopia Profile Editor [21].

All these stated authoring formats are not extensible. Extensibility of a format is critical for its acceptance, which helps various communities to adopt a simple base format and bring in changes from the domain-specific requirements. Also, it will help to generate various standard formats from the same source document without just depending on the mutually inclusive elements.

Chapter 3

Problems and Challenges in MAP Authoring

3.1 Challenges in Metadata Application Profile Creation

Dublin Core Metadata Initiative (DCMI) defines one of the earliest guidelines with Description Set Profiles (DSP), a constraint language for Dublin Core Application Profiles based on the Singapore framework for application profiles. [17] Even though there are definite needs and guidelines to create application profiles, especially machine actionable, the number of publicly accessible application profiles are fewer than it should be. Also, there is a lack of availability of machine-friendly DSP. One of the main reasons is because of the lack of simplified workflows or tools, due to which the task of application profile generation is tedious and with fewer incentives. Other significant challenges with application profiles are versioning, change management, and machine-friendly changelogs. Application profiles are often created with human visual-oriented tools such as word processors or spreadsheets and serve the purpose of documentation other than being actionable. A preliminary investigation over available application profiles shows a clear need for simplified options to encourage metadata developers to adopt the actionable MAP development.

3.2 MAP creation for various domains

Evolution of linked data and adoption of metadata is encouraging different communities to extend their outputs to incorporate various metadata standards; in order to find new applications, approaches, and insights on their data. Different domain experts are already developing profiles suitable for their metadata applications. Developing MAPs are challenging for most of the domain experts as they may not be well aware of the concepts involved in application profile creation. Different communities have different levels of experience in the technical aspects

of application profit creation. A severe lack of guidelines on application profile creation and publishing exists. Also, the limited number of well-defined samples and initiatives to archive and curate application profiles is another blockade. There is not any popular interoperable format or preprocessor for creating application profiles. All these facts make application profile creation an expensive process with minimal incentives.

3.3 Limitation of existing Authoring formats

There are not many authoring formats for application profiles, and the available options are either minimal or specific to particular purposes. A general-purpose application profile authoring format is not yet wholly proposed by any other initiatives. Most of these authoring formats are either of limited functionality or highly optimized for a specific purpose. For example, in the case of simple DSP, the CSV input format is heavily optimized and simplified for encoding only bare minimal application profile information. Authoring environments such as Bibframe profile editor is useful for making the process simplified. On the contrary, bibframe profile editor or its variant Sinopia profile editor¹ are restricting the users to stick within the derived framework of bibframe profiles. Even though they are useful in creating application profiles in general-purpose, it requires a significant level of expertise in creating application profiles.

3.4 Provenance and Change logs

Creating and maintaining changelogs of application profile versions help to assure the longevity of the metadata. The longevity of the schema is a significant part of metadata longevity. The provenance of metadata schema should be documented and managed for metadata preservation. [12]. If the changelogs are created in an actionable format, it can be used for different purposes such as creating human-readable changelogs to automated schema migrations. A record of application profile changes is also a record of the metadata changes. Maintaining change logs for different versions is as crucial as maintaining accessible formats of the versions itself. Changelogs help to migrate datasets to new profiles or create crosswalks to upgrade the instances. For LOD, changelogs help to update linked datasets as well. Changelog permits efficient migration of instances by only migrating the changed parts.

¹<https://profile-editor.sinopia.io>

Chapter 4

Proposed Solutions

Upon a close examination of previous attempts to promote MAP development, some of the shortcomings were identified. Moreover, YAMA format is derived from the limitations of its predecessors. The most crucial challenge is to promote MAP acceptability in diverse communities to enhance interoperability and reuse of possible vocabularies.

4.1 Interoperable Formats

Lack of interoperable preprocessing systems for MAP is one of the prominent challenges. A preprocessor takes an input written using some simple language syntax and output another format following the syntax of another language specifications. A preprocessor extends the syntax of existing language by adding new syntactic constructions. The user writes the input format using the extended syntax, and then the processor translates it into one or more different formats. Some of the popular preprocessors are Markdown to process HTML [6], reStructuredText to process Python documentation [11]. Sass to generate CSS and CoffeeScript to generate JavaScript.

There are well-defined standards and specifications to create metadata specific markups and formats. For example, a MAP DSP can be represented in DC DSP XML, RDF or human-friendly spreadsheets and CSVs. However, the interoperability of DSPs is not assured, and there is no such preprocessor to handle the creation of these formats in a simplified way with fewer efforts. The limited number of application profile DSPs is mainly due to this reason.

4.2 Change logs and Roadmaps

Changelogs and roadmaps of application profiles are manually created and are often incomplete or not actionable. Changelogs of most of the publicly published application profiles are either available only as human-readable format or are

not maintained [12]. Integrating change log maintenance to application profile creation workflows will help the maintainers to keep them in a seamless way as well as generation of the various changelog formats can be automated. It can help to reduce errors and efforts in creating changelogs.

4.3 Tooling

For the creation and management of application profiles, there are recommendations such as Me4DCAP which provides a guideline to scope definition, construction, development, and validation[13]. However, tools or systems dedicated to MAP creations does not exist. Usually, application profile maintainers have to depend on various tools to generate specific formats. Dependency on different tools makes the whole process tedious for most of the domain experts; as a result, application profiles were authored in documentation format rather than machine-actionable.

4.4 Extendable Authoring Formats

A better authoring format, which includes the above-said solution, can be considered as the best and single-shot solution. Moreover, such authoring format should provide a dedicated preprocessor for application profiles as well as various similar formats. The best recommendation for such authoring format is, it should act as an authoring environment as well as a preprocessing format, with various options to import, export or render different formats and packages without depending on multiple tools or skills.

Chapter 5

YAMA: Yet Another Metadata Application Profile

This study proposes a YAML based authoring formats named Yet Another Metadata Application Profile (YAMA), an application profile authoring format to record, modify and version the MAP creation tasks. A custom YAML specification is used to hold various stages, levels, and releases of MAP.

The initial proposal was to define the MAP in a tabular matrix, but a tabular form of records comes with its own limitations. Primarily, it is difficult to build up semantics and hierarchical structure of the DSP in a single spreadsheet. The tabular form represents data in repetitive cells and rows. This matrix form is not nested and some additional efforts like splitting into multiple files or introducing some special notations required to encode hierarchical data in spreadsheets. Also, simple operations like diff or text comparison are complicated due to CSV's nature of holding multiple values in a single line. Eventually, YAML is adopted to represent the MAP. YAML is flexible, understandable text-based data serialization format, which makes it simple to integrate with version control systems like Git, as well as simple text editors to modify and record application profile related changes. The data expression capability of YAML is superior to that of CSV in many ways. For example, CSV expresses only simple tabular data in rows and columns, but YAML can represent complex data in simple key-value pairs to nested trees. Also, YAML natively supports comments and blank lines without impacting the data, and this makes it a suitable candidate as an authoring format. Being a text document, YAML can be used as it is for parsing, but various spreadsheets formats may need to be converted into CSV. YAMA can be easily created and maintained with text editors.

YAMA is not defined as a new standard of MAP, but YAMA is defined as an easy to use preprocessor to create standard MAP formats. YAMA is intended to be simple enough that domain experts can use it without extensive knowledge on MAP. YAMA attempts to solve the absence of an application profile authoring workflow. Considering the rising popularity of GitHub-based workflows, various

output formats and extensibility to various proposals like ShEx, DCAT, PROV and eliminate the need of repetitive tasks in application profile maintenance. YAMA is an intermediary format for generating or converting various existing standard formats of application profiles. YAMA is usable in other requirements like Data Catalog Vocabulary (DCAT) and CSV on the Web (CSVW), but not limited to these.

5.1 YAMA as an Authoring Format

Yet Another Metadata Application Profile (YAMA) is proposed by the authors as an extensible authoring format for application profile, which addresses some of the shortcomings of the previous proposals [25]. YAMA is intended to be simple enough that domain experts can use it without extensive knowledge on MAP. YAMA uses YAML Ain't Markup Language (YAML), which is a robust human-friendly data serialization standard with various implementations in most of the popular programming languages and considered as a superset of JSON [2].

YAMA is also an attempt to solve the absence of an application profile authoring workflow. Considering the rising popularity of GitHub-based workflows, various output formats and extensibility to various proposals like ShEx, DCAT, PROV eliminate the need for repetitive tasks in application profile maintenance. YAMA is an intermediary format for generating or converting various existing standard formats of application profiles.

YAMA is extensible with custom elements and structure. For example, custom elements can be added to the document tree, as per the demand of the use case. The only restriction is that custom elements cannot be from reserved element sets. This will help to extend the capabilities of YAMA without any large-scale implementation changes. Any such extension is possible within the scope of YAML specification. YAMA is based on DC-DSP, and a minimal DC-DSP is mandatory to express a MAP in YAMA. Along with the extensible key-values and structure YAMA also includes a structured syntax to record modifications of a YAMA document named as change-sets. YAMA change-sets can be used to record changes of a MAP over any other versions. Change-sets are adapted from RFC 6902 JavaScript Object Notation (JSON) Patch [18], with the changes marked as an action to a path. Every change use ‘status’ as a reserved value to indicate status changes like ‘deprecation.’ This extensible nature of YAMA documents is explained in Figure 5.1.

5.2 YAML as a Promising Format

YAML Ain't Markup Language (YAML)¹ is a robust human-friendly data serialization standard with various implementations in most of the popular programming

¹<https://yaml.org/>




Figure 5.1: Extensibility of a YAMA Application Profile

languages. As per the latest specification - version 1.2², YAML is considered as a superset of JSON [2]. The strict adherence to readability makes YAML a superior choice of data serialization format for manual creation and modifications. The popularity and acceptance of YAML over JSON are growing in recent years due to its flexibility to express structured data in a textual way without complex syntaxes. Unlike CSV, YAML is friendlier with version control systems like Git and text editors. Being an open format, it prevents any vendor locking on the documents and permits the development of methods and systems to interact with the YAML documents programmatically.

YAML is adapted as a format for projects like OpenAPI Specification (OAS)³ which defines a standard interface to RESTful APIs [10], YARRRML which is a human-readable text-based representation for declarative Linked Data generation rules [8]. and Dead simple OWL design patterns (DOS-DP)⁴ which is a simple system for specifying OWL class design patterns [19].

Application profiles are supposed to be structured documents with a descriptive logic. An Application profile written in YAML is structured without any complicated processing. Also, the potential of comments, syntax formatting and highlighting with modern text editors will help to keep the visual and logical organization of an application profile considerably more comfortable. YAML can make a YAMA document self-explanatory and by itself acts as a documentation for the development of MAP.

5.3 Extensibility of YAMA

Extensibility of a format is the critical element for its acceptance, similar to the philosophy of Dublin Core. Extensibility of an application profile is helpful for

²<https://yaml.org/spec/1.2/spec.html>

³<https://www.openapis.org/>

⁴https://github.com/INCATools/dead_simple_owl_design_patterns

various communities to adopt a simple base format and bring in changes from the domain specific requirements. Also, it will help to generate various standard formats from the same YAMA document without just depending on the mutually inclusive elements. As a use case, application profile creators can use YAMA as a single source preprocessor to generate various file types, formats, or specifications such as but not limited to DC-DSP, Bibframe JSON or Interactive web documentation.

YAMA is extensible with custom elements and structure. For example, to create constraints, elements from ShEx can be used in the form of structured YAML and custom elements can be added to the document tree, as per the demand of the use case. The only restriction is that custom elements cannot be from reserved element sets. This will help to extend the capabilities of YAMA without any large-scale implementation changes. Any such extension is possible within the scope of YAML specification. There is also a user variables section which is a straightforward approach to add any user-defined variables without altering the structure of a YAMA document.

5.4 Expected outputs for YAMA

YAMA document has different components which act as part of different output purposes. YAMA document has mandatory metadata for application profiles, section to record application profile, optional changesets to record changes between different versions and optional changelog for recording actionable changelog information. These sections can be used in various purposes, for example application profile metadata can be used to ensure provenance of the metadata the application profile. Same way ChangeSets and changelogs in conjunction with the administrative metadata of the application profile can be used to generate longevity information such as human-readable and machine actionable changelogs as well as different versions of the application profile. However the main functionality of YAMA document is to act as an authoring format for application profiles. This can be achieved by combining the administrative metadata part of the application profile and the application profile section of the document. This clearly illustrates the capability of YAMA to be an authoring format for metadata application profiles, as well as a suitable way to ensure provenance and longevity.

A detailed illustration of this components to output mapping is given in figure 5.2.

5.5 Possible use-cases for YAMA

YAMA acts as a meaningful and actionable authoring tool for MAP. As a preprocessor format, it serves as a source for MAP. A source format enhances the maintainability

of MAPs. Being YAMA, a structured textual format, YAMA fits well with collaborative development environments and version control systems. That makes the change tracking convenient with basic diff operations to advanced continuous integration systems. As a structured authoring format, YAMA makes it easy to validate the MAP and helps to eliminate errors and logical complexities.

YAMA's capability of recording optional change records will act as a development roadmap and will permit the generation of previous versions, actionable or human-friendly change logs as well as formats for metadata crosswalks and migrations. YAMA is also suitable to generate human-friendly documentation from the serialized source, with the help of templating or other means. As a template-first system, It is easy to customize the output formats. YAMA's extensibility helps to tailor it to suit for different community/use cases. Being TAML, a text-based format, YAMA is highly interoperable with various text editors/tools.

5.6 Advantages of YAMA as an authoring format

As an authoring format, YAMA significantly reduces the efforts required in authoring and maintaining application profile. YAMA helps to record an application profile into a highly flexible and extensible data-serialization format. Also allows generating the expressions of an application profile in various standard expressions, such as RDF, XML, ShEx, SHACL, and JSON. This simplification helps users with moderate skills in these formats to create application profiles with minimal efforts. As a result, the barriers involved - such as the cost, expertise, and other challenges - in application profile creation can be lowered.

Instead of proposing a new format for application profile, YAMA helps to record the core elements required to produce various existing standard formats and generate them. These expressions are created either using simple templates for the normal user or programmatically for advanced users. The significant advantage of YAMA is, it can be a single source for different expressions. A single source makes the maintenance of application profiles more comfortable than maintaining multiple independent formats.




Figure 5.2: Components of YAMA and their expected outputs

Chapter 6

YAMA Syntax and Specifications

6.1 Expressing Application Profiles in YAMA

YAMA specification defines textual syntax and specifications for writing YAMA documents in a natural text form. YAMA syntax is based on YAML 1.2 specification. YAMA is parsable with any YAML 1.2 parser, but processing capabilities of YAMA documents are limited to YAMA specific implementations. A complete specification for YAMA format is accessible at <https://purl.org/yama/spec/latest>.

A YAMA document should strictly follow YAML specifications. The document should start with a valid YAML declaration, and YAMA version should be mentioned before starting the structure of the document. If a valid YAMA specification version is not declared, then the last available version is assumed to be used.

YAMA document is structurally organized as Description Set metadata, namespaces, descriptions, statements, constraints, change sets and user defined values.

Metadata section is intended to express necessary information of the specific MAP. Generally, administrative metadata of the MAP is expressed as a key-value pair. Important property from this section is the version and creator. This information is used in generating publishable formats and creating provenance information as well as the changelog of the MAP.

Single resources are described under descriptions with a unique ID for each description. Every unique descriptions ID can have multiple key-value pairs to describe that resource. A statement is a single data element used to describe a resource that is defined as a description. The statement defines the possible values and any other constraints. A description can have one or more statements, but descriptions without any statements are not actionable. Constraints are reusable components and can be callable through their unique id. Multiple constraints can be mixed and matched to satisfy complex requirements, as well as constraints, are permitted to include custom key values or structures. Structure of a YAMA document is explained in figure 6.1 and example code for a YAMA document is given in figure 6.2.




Figure 6.1: Structure of YAMA Document

```

%YAML 1.2
---
#%YAMA 0.8

meta:
  id: dcat-ap
  title: DCAT Application Profile for Data Portals in Europe
  version: 1.2.1
  date: '2019-05-28'
  subject: Application profile for data portals in Europe (DCAT-AP)
  license: ISA Open Metadata Licence v1.1
  creator: DCAT-AP Working Group
  website: https://github.com/SEMICeu/DCAT-AP

# rest of the section is omitted in this example #

namespaces:
  adms: http://www.w3.org/ns/adms#
  dcat: http://www.w3.org/ns/dcat#
  dct: http://purl.org/dc/terms/

# rest of the section is omitted in this example #

constraints:
  voc_dataset_theme_vocabulary: &voc_dataset_theme_vocabulary
    type: vocabulary
    vocabulary_name: Dataset Theme Vocabulary
    URI: http://publications.europa.eu/resource/dataset/data-theme
    notes: The value to be used for this property is the URI of the vocabulary
      ↳ itself,
      i.e. the concept scheme, not the URIs of the concepts in the vocabulary.

# rest of the section is omitted in this example #

statements:
  pr_dataset: &pr_dataset
    label: dataset
    property: dcat:dataset
    range: dcat:Dataset
    description: This property links the Catalogue with a Dataset that is part of
      the Catalogue.
    min: 1
    max: n

# rest of the section is omitted in this example #

```

Figure 6.2: An example of a YAMA document




Figure 6.3: Structure of YAMA ChangeSets

6.2 Changesets in YAMA

YAMA also proposes syntax and specifications of Change-Sets. The change-sets concept can be explained as a structured syntax to record modifications of a YAMA document. YAMA change-sets can be used in preprocessing existing documents to create a modified version or use to record changes of a document over any other versions. Change-Sets is inspired from RFC 6902 JavaScript Object Notation (JSON) Patch [18], with the changes marked with an action to a path with an additional special reserved value as ‘status’ to indicate status changes like ‘deprecation.’ The structure of YAMA changeset is expressed in figure 6.3, and an example code snippet for changeset is shown in figure 6.4.

6.3 YAMA Use Cases and Aims

There are different use cases for a preprocessor in MAP creation; some of the possible scenarios can be listed as:

1. Acts as a meaningful and actionable authoring tool for MAP.
2. A preprocessor format acts as a source for MAP, which enhances the maintainability of MAPs.

```

changesets:
  cs_20181108_01:
    version: 1.2
    previous_version: 1.1
    date: 2018-11-08
    changes:
      ch_20181108_01:
        op: replace # remove, add, replace, copy, test
        path: /statements/pr_type/max
        value: n
        # Old value; applicable for replace, remove and copy
        previous_value: 0
        # extending a change
        notes: |
          UpdatesCardinality: 0..1 -> 0..n
          This property can be repeated in the
          case that multiple licence types
          apply to a licence document.
        URI: dct:type
        label: Recommended property (Licence Document)
        issue: [DCAT-AP-1, "https://github.com/SEMICeu/DCAT-AP/issues/1"]

```

Figure 6.4: Example of YAMA ChangeSet

3. A structured textual format, which fits well with collaborative development environments and version control systems, and makes the change tracking convenient with basic diff operations to advanced continuous integration systems.
4. A structured preprocessor format makes it easy to validate the MAP and helps to eliminate errors and logical complexities.
5. A preprocessor with optional change records will act as a development roadmap and will permit generation of previous versions, actionable or human-friendly change logs as well as formats for metadata crosswalks and migrations.

6.4 Integrating, Extending and Maintaining YAMA

YAMA is expressed in YAML, which is a simple text format. Application profile developers can use any standard text editor to create the YAMA format. Syntax highlighting, prettification, validation, and linting can be achieved with various tools. YAML fits well with Git-based workflows and is capable of handling comments as well as blank lines for readability. Using these features, YAMA can be used as a documentation and roadmap of application profile development. YAMA format can be programmatically generated from spreadsheets or other data formats. Some of these approaches were attempted to demonstrate through the proof of concept tool-kit.

6.5 Recommendations and Best Practices

YAMA documents should be versioned to utilize its capabilities on versioning, changesets, and changelogs. Semantic versioning (SemVer)¹ is highly recommended. Also, calendar versioning (CalVer)² can be considered if it fits the requirements. With the proper version number, YAMA processors can automate various versioning related tasks as well as can generate publishable versioned output formats. The version number should be used in output file(s) naming convention as well. A version named file is self-explanatory in URLs as well as Git-based authoring systems. Changesets specification strictly adheres to version numbers and a semantic logic on versioning. In semantic versioning approach MAJOR.MINOR.PATCH is considered in MAP as patch versions do not break any MAJOR, MINOR definitions with forward and reverse compatibility. It can be used internally as part of the development and for fixes and corrections related to typos and or less significant changes. However, public releases can follow MAJOR.MINOR approach with a MINOR being compatible within the same MAJOR releases. Changes which breaks the compatibility should strictly follow a MAJOR version change.

Various standard formats of application profiles are recommended to publish as a single package, accessible in a persistent web URL, which includes the profile id, version, format, and extension in a self-explainable way.

example :

```
http://example.com/ap/my-book-case_1.4/my-book-case_1.4_dsp.rdf  
http://example.com/ap/my-book-case_1.4/my-book-case_1.4_documentation.pdf  
http://example.com/ap/my-book-case_1.4/my-book-case_1.4.shex
```

¹<https://semver.org/>

²<https://calver.org/>

Chapter 7

YAMA Toolkit

A proof of concept toolkit is developed as a part of this research, in order to explain the practicality of the proposed YAMA format. This proof of concept toolkit is not intended to be a full-fledged solution of using YAMA, rather a demonstration of how some of the features proposed in YAMA can be useful. As YAMA is compatible with YAML 1.2, we anticipate that a YAMA document can be completely independent of a specific implementation but a highly adaptable format for any languages or toolkits. YAMA is intended to use or incorporate within existing workflows or workflows which requires highly customised outputs. This toolkit is under continuous development, and enhancements and fixes will be included as the acceptance of the format increases.

7.1 Python module & Command Line Interface

The proof of concept toolkit is developed as a Python package to work with YAMA specification. This Python package can be used as a module for Python application development, or as a command line tool to work with YAMA format files. This toolkit can parse a YAMA format and return structures applicant profile data or render the structured application profile using custom or built-in Jinja2 templates. Python package is available at <https://purl.org/yama/tools/pyyama>. With the use of the python package, other template system or advanced libraries such as but not limited to RDFLib¹ and PyShEx² can be used to process the parsed structure to generate or manipulate the formats programmatically.

A command line interface is made available within the Python package. This commandline interface is supposed to be used within congestion of other tools for example linting or formatting the output or included with the git automation. Still this CLI tool is a proof of concept of the actual capability of YAMA format. Some bare minimal functions, such as generating basic formats or rendering using Jinja

¹<https://rdflib.readthedocs.io>

²<https://github.com/hsolbrig/PyShEx>

templates. Functionality of this tool will be improved as long as the Python package gets updated.

7.2 Templates and generators

YAMA helps to generate outputs programmatically or using temples. Templates are the easiest option for domain experts, who are less experienced in various output formats. Authors experimented with temples for various format and observed that the output is as good as programmatically generated counterparts. This approach makes customization of output easier for various communities by rather editing the temples than going through any programming challenges.

Templating based approach is helpful for creating actionable formats like RDF-OWL, XML and JSON-LD. Also, the templates make it easy to render human friendly HTML pages as a web publication medium and can be converted into printer friendly formats like PDF. For advanced users, various tools can be used to achieve desired output formats.

To maintain simplicity, but to ensure extensibility and customization capabilities YAMA Python toolkit can use templates to generate any formats from the parsed structured application profile data. Templates permit to generate virtually any formats without the complexities of dealing with complex libraries. YAMA toolkit uses Jinja2³ templates by default. Jinja2 a full featured and one of the most used template engines for Python. It is fast, widely used, and secure with a configurable syntax and logic [22]. Originally Jinja2 is designed for HTML templates, but it is suitable for all kind of text-based formats. Using Jinja2 templates, not only HTML but complex RDF or JSON data files can be generated. Some of the standard formats are provided as ready to use templates. The tool-kit will be updated with more templates depending on various use-cases. An example for a simple Jinja template is given in 7.1.

Advanced users can use any Python templating systems to extend the package's templating, or custom python scripts to render the structured AP without templates. The package can optionally use generator scripts other than templates, which are python scripts to generate output formats or packages programmatically without templating. A generator can use complex programming logic or depend on external libraries or programs to generate the desired output.

³<http://jinja.pocoo.org/>

```
<?xml version="1.0" ?>
<DescriptionSetTemplate xmlns="http://dublincore.org/xml/dc-dsp/2008/03/31">
{%
    for key, description in dsp.descriptions.items() %
        <DescriptionTemplate>
            {% for key, statement in description.statements.items() %}
                <StatementTemplate>
                    <Property>{{ statement.property }}</Property>
                </StatementTemplate>
            {% endfor %}
        </DescriptionTemplate>
    {% endfor %}
</DescriptionSetTemplate>
```

Figure 7.1: A basic Jinja template example

Chapter 8

Related Works

Proposal of YAMA as an extensible authoring format for metadata application profiles, is based on the understanding and analysis of some of the previous and related studies and projects. Some of the important attempts to define application profiles and to help creating application profiles were reviewed as part of this research. These proposals were influenced the idea of YAMA, also we attempted to solve most of the shortcomings of these attempts. YAMA has its own differences and advantageous compared to most of these attempts.

8.1 DCMI Description Set Profiles

The Dublincore Metadata Initiative Description Set Profile describes an information model and XML expression of a Description Set Profile (DSP), based on the DCMI Abstract model. A DSP is a means of describing constraints on a description set. It constrains the resources that may be described by descriptions in the description set, the properties that may be used, and the ways a value surrogate may be given. A DSP can be used as a formal representation of the constraints of a Dublin Core Application Profile, configuration for databases, and metadata editing tools [17].

Even though, DSP does not act as human-readable documentation or definition of vocabularies as well as version control of the metadata instance. A DSP contains only syntactic constraints and need to combine with human-readable information, usage guidelines and version management for using as an application profile. Basic structure of DSP is expressed in figure 8.1.

YAMA built on top of DCDSP, and strictly adhere to any future updates on DCDSP. The basic structure of YAMA is DCDSP and it attempts to extend the DSP to include changes logs, versioning and human readable documentation generation. DCDSP doesn't define any specific authoring environments or formats, but this research is more on defining an extensible authoring format.




Figure 8.1: Basic structure of DC Description Set Profiles, a constraint language for Dublin Core Application Profiles

8.2 Metabridge Simple DSP (SDSP)

Metabridge¹ is a metadata schema registry to support sharing of metadata schemas and promote reuse of metadata schemas and support metadata interoperability. Metabridge is based on the Singapore Framework of application profiles. Metabridge project defined Simple DSP (SDSP) a simplified DSP authoring format in spreadsheets². Metabridge SDSP can be processed with the metabridge web service to obtain RDF expression as well as the website can display the application profile in a human friendly manner [15].

YAMA is highly influenced by the simplicity of SDSP and a continuation of attempting more machine actionable and structure format to simplify the authoring of application profiles. This also intended to solve the limitation of a tabular format to express a structured document like application profile. Also YAMA can be parsed without any custom implementation as it is YAML 1.2.

8.3 Me4DCAP

Me4DCAP aims the design of a method for the development of Dublin Core Application Profiles. Me4DCAP can be considered as a starting point to Singapore

¹<https://metabridge.jp>

²http://www.soumu.go.jp/main_content/000132512.pdf

framework for DCAP and integrates principles from the modes of the metadata community concerning DCAP development and software development processes and techniques. Me4DCAP establishes a way for the development of a DCAP such as, the activities involved in application profile creation, when they should take place, how they interconnect, and which deliverables they will bring about. It also suggests which techniques should be used to build these deliverables [13].

Me4DCAP defines only the methods involved and deliver a theoretical framework for the application profile creation. The concepts of an extensible authoring format is inspired from the methods from Me4DAP. However, Me4DCAP doesn't resolve the challenges involved in authoring formats or authoring workflows for application profiles.

8.4 IMI Data Model Description (DMD)

Data Model Description (DMD)³ is a package to explain the data model. DMD is developed as part of IMI(Infrastructure for Multilayer Interoperability) Common Vocabulary Framework to describe common terms and their relationship in order to enhance the interoperability of open data and Digital Government in Japan. DMD is created to share the data model and to unify the data model to ensure data interoperability and utility value. DMD also plays the role of bridging the gap between humans and computers by providing a machine and human readable package of data model definition. A translated diagram⁴ to explain the DMD package structure is given in figure 8.2.

DMD is not adhering to Singapore framework; also, it is not a complete application profile. DMD has a well-defined editor and related tools as an authoring environment⁵. The package concept of DMD influences the package concept of YAMA best practices, in delivering Application Profiles as a package with different expression formats.

8.5 Bibframe Profile Editor

Library of Congress Bibframe Profile Editor⁶ is a graphical profile editor developed for the specific needs of Bibframe community to modify existing profiles or to create a new profile. Bibframe editor is mainly for the profiles of the BIBFRAME vocabulary, but usable for other profiles as well. See figure 8.3.

³<https://imi.go.jp/goi/datamodel-about/>

⁴https://imi.go.jp/contents/2019/02/DMDSpecification_V301_20190228.pdf

⁵<https://imi.go.jp/goi/dmd-editor/>

⁶<http://bibframe.org/profile-edit/#/profile/list>




Figure 8.2: Package structure of DMD (Translated)




Figure 8.3: DCAT-AP in BIBFRAME Profile Editor

Chapter 9

Comparison & Evaluation

To evaluate the advantage of YAMA as an extensible authoring format for application profiles, three different formats were compared. They are Simple DSP [15], Bibframe Editor [3] and YAMA [25]. These three proposals were intended to improve and simplify the process of metadata application profile creation. The three formats use spreadsheets, web interface, and text editor as an authoring environment to express the source. Detailed comparison of these three authoring formats is given in Table 9.1.

One of the major public application profiles, The DCAT Application Profile (DCAT-AP) for data portals in Europe [26] was selected as sample application profiles for the evaluation. The selection is based on its popularity, active maintenance, and the availability of previous versions. DCAT-AP is released as human-readable documentation as well in different machine actionable expression formats such as JSON-LD, RDF and SHACL. Since the source of this application profile is not available, it was assumed that DCAT-AP is created not using any authoring tools but rather manually using word processors and editors for individual formats. To conduct this evaluation, the authors attempted to recreate DCAT-AP using all three authoring formats and used the created source to generate standard application profile expression formats with corresponding tools. This recreation process used human-friendly documentation of the application profiles and tried to include maximum information as the corresponding authoring format permits.

An analysis of the outputs was conducted by comparing the generated expression formats to its originally published versions and documentation. This analysis aimed to identify if an extensible authoring format can express real-world application profiles better than its non-extensible counterparts. The evaluation is performed by comparing the authoring process with these formats, and the extent of information these formats could reproduce from the documentation.

Table 9.1: Feature comparison of three authoring formats used for evaluation.

	SDSP	Bibframe	YAMA
Based on Format Standard	DC-DSP CSV RFC-4180	Bibframe JSON RFC-8259, ECMA-404	DC-DSP YAML YAML 1.2
Strict to standard	No	Yes	Yes
Comments	Yes	No	Yes
Blank lines	Yes	Yes	Yes
Line Diff	Partial	Yes	Yes
Standard library compatibility	Partial	Yes	Yes
Native logic	No	Yes	No
Text editor compatibility	Partial	Yes	Yes
Native Syntax highlighting	No	Yes	Yes
Custom Editor	No	Yes	No
Proposed Editor	Spreadsheet	Bibframe Profile Editor	Text Editor
Schema Validation	No	Possible	Possible
Readability	Low	Low	High
Extensible	No	No	Yes

9.1 Results

Three authoring formats were used in creating a known application profile (DCAT-AP) sources from the documentation and their capability to include the documented application profile features and details were evaluated. The results shown from the investigation can be categorized into a) the capability of including details from the documentation, b) convenience as an authoring format, c) capabilities of producing relevant expression formats.

Three of these formats could represent part of the documentation but mostly the textual explanations and general sections form the documentation is ignored for the convenience, with an assumption that it is manually maintained. All three authoring formats are initially designed for the Dublin Core Application Profile (DCAP), and the application profile evaluated was not entirely Dublin Core Application Profiles. However, for the evaluation, the authors attempted to include maximum information without altering the DCAP structure, wherever possible.

A general observation from the expression capability can be summarized as all three formats could express the essential elements from the documentation and simple DSP could express the minimal information of the AP, and could not express most of the components from the documentation. BibFrame Profile editor could express the full application profile, but semantics including the classes and its statements had to be represented as resources and statements. Also, specific hierarchical structures such as ‘mandatory’, ‘recommended’, and ‘optional’ status of the classification of the statements was skipped and represented the application profile structure more specific to BibFrame. YAMA is extensible due to its straight adaption of YAML, so every section from the application profile documentation

```

classes:
  cl_agent: &cl_agent
    label: Agent
    property: foaf:Agent
    requirement: mandatory
    reference: [http://xmlns.com/foaf/spec/#term_Agent, http://www.w3.org/TR/vocab-org/]
    notes: An entity that is associated with Catalogues and/or Datasets. If the Agent is an organisation, the use of the Organization Ontology is recommended. See section 7 for a discussion on Agent roles.
  mandatory_properties:
    - *pr_name
  recommended_properties:
    - *pr_licence_type
cl_catalogue: &cl_catalogue
  label: Catalogue
  property: dcat:Catalog
  requirement: mandatory
  reference: http://www.w3.org/TR/2013/WD-vocab-dcat-20130312/#class-catalog
  notes: A catalogue or repository that hosts the Datasets being described.
  mandatory_properties:
    - *pr_dataset
    - *pr_description

```

Figure 9.1: Classes from DCAT-AP shows extensibility of YAMA

could be included, and custom names could be used for the keys from the profile's own naming conventions. For an example, part of the document is shown in Figure 9.1.

With respect to the editing process involved, SDSP is found to be relatively easy due to its spreadsheet-based nature which is expressed in CSV, and a spreadsheet editor was used in the process. However, BibFrame Profile Editor is a direct application profile editor with an interactive web-based user interface and advanced suggestion systems to help the profile creation process. Also, BibFrame profile editor supports selecting vocabularies for pre-populating the fields as well as it permits to edit the application profile in a well-structured way. Both in SDSP and YAMA, the structure of the profile is logically built through the syntax specification, but in BibFrame editor the structure is built through visual interaction. A screen shot of the BIBFRAME profile editor is shown in Figure 8.3.

As part of the evaluation, two different sets of use-cases were identified. The first set of use-cases, which are general for an application profile authoring format, and the second set is about extensible authoring formats. All three authoring formats in this study were compared against these use cases. Detailed results for the comparison of the first set is given in Table 9.2, and the comparison for extensible authoring format use cases are in Table 9.3.

Table 9.2: Comparison of general use cases for application profile authoring formats.

Use-cases	BIBFRAME Profile Editor	Simple DSP (SDSP)	YAMA
Acts as a meaningful and actionable authoring tool for MAP.	Yes (Web UI)	Yes (CSV)	Yes (YAML is actionable and human readable.)
A preprocessor format acts as a source for MAP, which enhance the maintainability of MAPs.	Yes (Import and Edit Bibframe JSON)	Yes (CSV)	Yes (YAML is a main-tainable format)
A structured textual format, which fits well with collaborative development environments and version control systems, and make the change tracking convenient with basic diff operations to advanced continuous integration systems.	Yes (JSON is less human friendly, but structured and maintainable)	Limited (Limitations of tabular format is applicable in version control systems.)	Yes (YAML is structured and suitable with version control systems)
A structured authoring format makes it easy to validate the MAP and helps to eliminate errors and logical complexities.	Yes (Bibframe Editor is suitable to limit errors. And JSON files can be validated.)	No (CSV formats has limited support with schema validation.)	Yes (Any YAML schema validator can be used.)
An authoring format with optional change records will act like a development roadmap and will permits generation of previous versions, actionable or human-friendly changelogs as well as formats for metadata crosswalks and migrations.	No	No	Yes (ChangSet format permits mainten-ance of actionable changelogs.)

Table 9.3: Comparison of use cases for extensible MAP authoring formats.

Use-cases	BIBFRAME Profile Editor	Simple DSP (SDSP)	YAMA
A authoring format to generate human friendly documentation.	No	No	Yes (Using templates suitable for required human friendly formats.)
A template driven system, to customize the output formats.	No(But the JSON file can be programmatically parsed to use with templating systems.)	No (Separate logical parser and a templating system are required.)	Yes (YAMA toolkit natively supports Jinja2 template system. As well as the structure of YAMA is optimized for template based output.)
Extensibility of the format to customize it to suit for different community/use-cases.	No(Limited to the scope of BibFrame community.)	Limited (Communities can use it but extensibility is not supported.)	Yes (YAMA permits extending or adding custom key-values in the YAML structure, as per the template requirements)
Inter-operable with various editors/tools	Limited (The output JSON can be edited in any text editors, but intended to work with the web-ui.)	Limited (Editable as a spreadsheet, but difficult to use with text editors.)	Yes (YAML is editable in any text editor and all popular text editors support, highlighting and proper indenting.)
Adherence to Singapore Framework	No (Only basic application profile.)	No (MetaBridge can generate owl format.)	Partial (Templates and generators can cover most of the Singapore Framework aspects.)

Table 9.4: Support for provenance description

Feature	SDSP	BIBFRAME	YAMA
Administrative Information	No	Limited	Yes
Version Details	No	No	Yes
Release Date	No	Yes	Yes
Change Records	No	No	Yes
Change Logs	No	No	Yes

9.2 Versioning, Changelogs and Provenance

Provenance information is vital for application profiles. Maintaining change logs of application profile versions help to assure the longevity of the metadata. The longevity of the schema is essential for metadata longevity. Metadata schema provenance should be documented and maintained for the preservation of metadata [12]. Application Profile should provide sufficient administrative information, such as creator, date of release, version, and usage rights. Versioning of the application profile is crucial as it is a record of an application profile as well as metadata changes. Keeping changelogs might help to migrate data-sets to new profiles or create crosswalks to upgrade the instances. For Linked Open Data (LOD), changelogs help to update linked datasets as well.

As an extensible format, YAMA can express version details with custom administrative information of the application profile. Also, YAMA records changes in a machine-actionable way, as well as readable changelogs. From the evaluation, it is clear that YAMA has the advantage of expressing, versioning, administrative details, release dates, change logs as well as actionable change records in the form of changesets. A tabular representation of a comparison of provenance among the three authoring formats are provided in Table 9.4.

Chapter 10

Discussion

YAMA is developed to be a direct adaption of DC-DSP. It is heavily inspired by the Simple DSP (SDSP) format developed for the MetaBridge project [15]. YAMA is an attempt to promote the acceptance of application profile concepts to various communities with less technical expertise. As a simplified format, it is not free from the limitations of expressing complicated application profiles or use cases. However, advanced users can still create them manually or use YAMA programmatically to overcome such limitations. Improvements for the YAMA specification and toolkit is being investigated. The modular structure is expected to expand to more object-oriented design compatible with the simplified format. Also, the toolkit will include some of the standard libraries to provide to deliver some of the advanced features.

Even though YAMA is efficient in authoring application profiles, YAML format and the structure could pose a challenge to editors. In other words, the ideal user of YAMA would need to be comfortable editing YAML directly, that requires the users to have the expertise of using a real text editor.

The evaluation suggests that authoring formats can significantly reduce the overall efforts in application profile creation as well as in compelling production of different expression formats. Three different types of authoring formats where evaluated and a considerably larger application profile is recreated using them. Compared to the other two constrained formats, as an extensible authoring tool for application profile, YAMA could express most of the documentation in an actionable manner. Limitations from the other two formats lead in dropping out most of the elements from the documentation and thus, permitting only a part of the human-readable documentation to be recreated. In YAMA, custom key-value pairs were used to include some aspects of the documentation, but in SDSP the structure is constrained so that it cannot be treated as an extensible option to add any custom information other than those specified in the SDSP structure. Similarly, the BIBFRAME profile editor does not permit to interact with the underlying structure and limits the user to follow a specific input process which the GUI is designed for.

The authors could programmatically obtain a structured application profile

definition from the YAMA document with native YAML processing libraries. However, SDSP required MetaBridge service to generate RDF expression of the application profile. BIBFRAME editor's output is JSON, and it could be parsed using standard libraries; however, to create different formats, advanced processing of the data is required, and it is possible but tedious.

10.1 Continuation and future plans

YAMA specification is a living standard, and it is getting updated as per the available use-cases. Continues updates and maintenance of YAMA specification as well as improving YAMA toolkit is planned. Activities to develop more examples, templates, and toolkit extensions will be continued.

Sample files created as part of this study is published at:
<http://purl.org/yama/examples>.

Chapter 11

Conclusion

MAP is getting a lot of popularity and acceptance in different communities. YAMA format is an attempt to express the idea of simplifying the tooling to support some of the tedious processes involved in creating and maintaining application profiles. Compared to its predecessors, YAMA provides an authoring environment, format, and provision for a toolkit for application profiles. Evolution of proposals like ShEx and DC-DSP2¹ give application profile more use cases and functions.

The developments in LOD promote data exchange and interoperability of data among communities. Application profiles are the most suitable means for ensuring interoperability and bringing in better use cases for data. Introducing easy to create and maintainable authoring formats will help different communities to adopt application profiles to express their data. There are evolving use cases for application profiles other than just explaining the metadata instance. Extensible authoring formats are expected to provide much more coverage for these emerging use cases, and it will also help communities to generate different formats or type of documentation from a single source which may serve much more purposes than just creating application profiles. The scope of an extensible format is futuristic, and also it can cater to various other demands related to metadata instances. Easy-to-use tools will also promote domain experts to create and publish application profiles in different machine-actionable expressions as well.

¹<https://github.com/dcmi/dcap>

Acknowledgement

First and foremost I want to thank my wonderful advisors Tetsuo Sakaguchi and Mitsuharu Nagamori. It has been a great experience to be their student. I appreciate all their contributions of time, ideas, expertise, care, and patience to make my master's program productive and enjoyable and also for granting me unconditional academic and personal freedom. They perfectly shaped my random thoughts into actionable concepts and nurtured them to meaningful research. I am very thankful to the two of them for undertaking this venture of leading me through this thesis.

I am wholeheartedly thankful to Prof. Shigeo Sugimoto for his guidance, helpful comments, informative pointers, and especially for his constructive criticisms.

I express my sincere gratitude to Tom Baker of DCMI for his support, feedbacks, and time, which significantly helped me in improving this research project. I am also indebted to Karen Coyle for her discussions, and ongoing continues efforts to improve DC-DSP, which gave a solid future and direction for this study.

The members of the MDLab have contributed immensely to my personal and academic time at Tsukuba. The group has been a source of friendships as well as sound advice and collaboration. I would like to mention specially and thank both of my tutors, Ryota Kinjo and Yuki Yamanaka for their understanding and helps in the last two years of my student life. I am also thankful to Shohei Toyota for sharing his valuable expertise, which helped a lot in developing some of the fundamental knowledge required for this research. My hearty regards for various helps from Mihara Tetsuya and Chiranthi Wijesundara.

I sincerely thank Prof. Morishima Atsuyuki and other members of the combined lab seminars for their comments and involvements during the presentation sessions.

This acknowledgment won't be complete without mentioning Dr. Beena Cherukuth for being my mentor over a decade and her influences in developing keen academic interests in Library and Information Science. My awesome dear people - Vijoy, Jollyettan, Rahman, Rajenish, Vava and my mother - for being at my side. In the absence of them, I would not be where I am today.

I dedicate this thesis and the time I spent for this Master's program to my late father - the coolest teacher I ever knew - for always encouraging me to pursue higher education and forced me to believe in 'better late than never.' I love you, you are the rock-star of my life ;).

At last but not least, my personal achievements entitled to this research are credited to my partner Deepa for her love, support, encouragement, companionship, and debates, which helped me to overcome all hardships and finally, made this thesis possible.

Nishad, T R
University of Tsukuba
July 2019

References

- [1] Murtha Baca. *Introduction to Metadata*. en-US. InteractiveResource. July 2016. URL: <http://www.getty.edu/publications/intrometadata> (visited on 04/10/2019).
- [2] Oren Ben-Kiki, Clark Evans, and Ingy döt Net. *YAML Ain't Markup Language (YAML™) Version 1.2*. Oct. 2009. URL: <https://yaml.org/spec/1.2/spec.html> (visited on 04/10/2019).
- [3] *BIBFRAME Profile Editor*. 2018. URL: <http://bibframe.org/profile-edit/> (visited on 06/14/2019).
- [4] Karen Coyle. *RDF-AP*. original-date: 2017-01-12T15:38:41Z. Jan. 2017. URL: <https://github.com/kcoyle/RDF-AP> (visited on 05/15/2019).
- [5] Fredrik Enoksson. *DCMI: A MoinMoin Wiki Syntax for Description Set Profiles*. Oct. 2008. URL: <http://www.dublincore.org/specifications/dublin-core/dsp-wiki-syntax/> (visited on 03/10/2019).
- [6] John Gruber. *Daring Fireball: Markdown*. URL: <https://daringfireball.net/projects/markdown/> (visited on 05/14/2019).
- [7] Rachel Heery and Manjula Patel. “Application Profiles: Mixing and Matching Metadata Schemas”. In: *Ariadne* 25 (2000). ISSN: 1361-3200. URL: <http://www.ariadne.ac.uk/issue/25/app-profiles/> (visited on 04/03/2018).
- [8] Pieter Heyvaert et al. “Declarative Rules for Linked Data Generation at Your Fingertips”. en. In: *The Semantic Web: ESWC 2018 Satellite Events*. Ed. by Aldo Gangemi et al. Vol. 11155. Cham: Springer International Publishing, 2018, pp. 213–217. DOI: 10.1007/978-3-319-98192-5_40. URL: http://link.springer.com/10.1007/978-3-319-98192-5_40 (visited on 05/17/2019).
- [9] Diane Hillmann. *Metadata standards and applications*. publisher: Metadata Management Associates LLC. 2006. URL: <http://managemetadata.com/> (visited on 04/25/2019).
- [10] OpenAPI Initiative. *OpenAPI Specification*. Aug. 2011. URL: <https://swagger.io/specification/> (visited on 05/14/2019).
- [11] Richard Jones. *A ReStructuredText Primer Docutils 3.0 documentation*. URL: <https://docutils.readthedocs.io/en/sphinx-docs/user/rst/quickstart.html> (visited on 05/14/2019).
- [12] Chunqiu Li and Shigeo Sugimoto. “Provenance description of metadata application profiles for long-term maintenance of metadata schemas”. en. In: *Journal of Documentation* 74.1 (Jan. 2018), pp. 36–61. ISSN: 0022-0418. DOI: 10.1108/JD-03-2017-0042. URL: <http://www.emeraldinsight.com/doi/10.1108/JD-03-2017-0042> (visited on 05/17/2019).
- [13] Mariana Curado Malta and Ana Alice Baptista. “A Method for the Development of Dublin Core Application Profiles (Me4DCAP V0.2): Detailed Description”. en. In: (2013), p. 14.
- [14] Mariana Curado Malta and Ana Alice Baptista. “A panoramic view on metadata application profiles of the last decade”. en. In: *International Journal of Metadata, Semantics and Ontologies* 9.1 (2014), p. 58. ISSN: 1744-2621, 1744-263X. DOI: 10.1504/IJMSO.2014.059124. URL: <http://www.inderscience.com/link.php?id=59124> (visited on 05/17/2019).
- [15] Mitsuharu Nagamori et al. “Meta-Bridge: A Development of Metadata Information Infrastructure in Japan”. en. In: (2011), p. 6.

- [16] Mikael Nilsson. *DCMI: Description Set Profiles: A constraint language for Dublin Core Application Profiles*. Mar. 2008. URL: <http://www.dublincore.org/specifications/dublin-core/dc-dsp/> (visited on 03/01/2019).
- [17] Mikael Nilsson, Tom Baker, and Pete Johnston. *DCMI: The Singapore Framework for Dublin Core Application Profiles*. Jan. 2008. URL: <http://dublincore.org/specifications/dublin-core/singapore-framework/> (visited on 05/17/2019).
- [18] Mark Nottingham and Paul Bryan. *JavaScript Object Notation (JSON) Patch*. en. Apr. 2013. URL: <https://tools.ietf.org/html/rfc6902> (visited on 03/17/2019).
- [19] David Osumi-Sutherland et al. “Dead simple OWL design patterns”. In: *Journal of Biomedical Semantics* 8.1 (June 2017), p. 18. ISSN: 2041-1480. DOI: 10.1186/s13326-017-0126-0. URL: <https://doi.org/10.1186/s13326-017-0126-0> (visited on 05/17/2019).
- [20] Andy Powell et al. *DCMI: DCMI Abstract Model*. 2007. URL: <http://www.dublincore.org/specifications/dublin-core/abstract-model/> (visited on 05/01/2019).
- [21] Linked Data for Production 2 (LD4P2). *Sinopia Profile Editor*. 2019. URL: <https://profile-editor.sinopia.io/> (visited on 06/14/2019).
- [22] Armin Ronacher. “Jinja2 Documentation”. In: *Welcome to Jinja2—Jinja2 Documentation (2.8-dev)* (2008). URL: <http://jinja.pocoo.org/>.
- [23] L. and R. Verborgh Svensson. *Negotiating Profiles in HTTP*. en. Mar. 2017. URL: <https://profilenegotiation.github.io/I-D-Accept--Schema/I-D-accept-schema> (visited on 05/17/2019).
- [24] Lars G Svensson, Rob Atkinson, and Nicholas J Car. *Content Negotiation by Profile*. Apr. 2019. URL: <https://www.w3.org/TR/dx-prof-conneg/> (visited on 05/15/2019).
- [25] Nishad Thalhath, Mitsuharu Nagamori, and Tetsuo Sakaguchi. *YAMA: Yet Another Metadata Application Profile*. 2019. URL: <https://purl.org/yama/spec/latest> (visited on 05/09/2019).
- [26] *The DCAT Application profile for data portals in Europe (DCAT-AP)*. original-date: 2017-09-13T07:53:27Z. Apr. 2019. URL: <https://github.com/SEMICeu/DCAT-AP> (visited on 06/14/2019).

Appendices

Appendix A : YAMA Specification

YAMA: Yet Another Metadata Application Profile

Finding, 20 May

This version: <http://purl.org/yama/spec/latest>

Issue Tracking: <https://github.com/nishad/yama/issues/>

Version: 0.1.4

<http://creativecommons.org/publicdomain/zero/1.0/> CC0 1.0 Universal (CC0 1.0) Public Domain Dedication

1. YAMA Specification

This document defines textual syntax and specifications for writing YAMA documents in a natural text form. YAMA syntax is based on [YAML 1.2 specification] (<https://yaml.org/spec/1.2/spec.html>). YAMA is parsable with any YAML 1.2 parser, but processing capabilities of YAMA documents are limited to YAMA specific implementations.

2. Status of This Document

This document is a part of the YAMA documentation. This document defines textual syntax and specifications. This is a working draft.

3. Introduction

3.1. Philosophy of YAMA

Yet Another Metadata Application Profile (YAMA) is not defined as a new standard of metadata application profiles; but YAMA is defined as an easy to use preprocessor to create standard metadata application profile formats. YAMA intended to be simple enough that it can be used by domain experts without extensive knowledge on metadata application profiles.

3.2. Syntax Compatibility

Instead of introducing its own syntax, YAMA adapts popular YAML format to avoid reinventing the wheel. Being a well proven data serialization format, YAML is widely accepted and various implementations are available for different programming languages. YAMA intended to get benefited from YAML's readability and human friendliness. As a superset of JSON, YAML is a comfortable choice to express complex structures in a human readable yet machine friendly way.

3.3. Extendability

YAMA is extendable with custom elements and structure. The only restriction is custom elements cannot be from reserved element sets. This will help to extend the capabilities of YAMA without any large-scale implementation changes. Any such extension is possible within the scope of YAML specification.

There is also a user variables section which is a straightforward approach to add any user defined variables without altering the structure of a YAMA document.

3.4. Specification Versioning

YAMA specifications adhere to [Semantic Versioning 2.0.0](<https://semver.org/spec/v2.0.0.html>), where MAJOR.MINOR stands for specification versions and PATCH for corrections and changes of the documentation, which doesn't break any implementations.

MAJOR version changes will affect the core specification, and MINOR version changes will be backward compatible and does not affect any previously implemented specifications.

4. Document Structure

A YAMA document should strictly follow YAML specifications. document should start with a valid YAML declaration and YAMA version should be mentioned before starting the structure of the document. if a valid YAMA specification version is not declared, then the last available version is assumed to be used.

```
%YAML 1.2
---
YAMA : 1.0
```

4.1. Metadata of the Application Profile

Metadata section is intended to express basic information of the specific metadata application profile. generally administrative metadata of the MAP is expressed as a key value pair. Important property from this section is the version and creator. This information is used in generating publishable formats and creating provenance information as well as change-log of the metadata application profile.

YAMA documents MUST be versioned. [Semantic versioning (SemVer)](<https://semver.org/>) is highly recommended optionally [calendar versioning (CalVer)](<https://calver.org/>) can be considered if it fits the requirements. With the proper version number, YAMA processors can automate various versioning related tasks as well as can generate publishable versioned output formats. See table 1 for list of elements in YAMA application profile metadata.

```
description_set :
  ID : # (R) A unique ID for the Description Set. eg :
    ↳ MyBookCaseDS.
  title : # Name of the AP. eg : My Book Case Application
    ↳ Profile.
  version : # Version following semver.org Semantic
    ↳ Versioning eg. X.Y.Z or X.Y or X.
  date : # Release date of AP. Any valid ISO-8601
    ↳ string.
  subject : # Subject or topic.
  creator : # Person, URL or more contact information. Can
    ↳ also be fname: Person, email: Email, org: Org}
  open : true # Open or closed DSP, will be respected in
    ↳ Application Profile curation services. Default true.
  license : # License of the DSP default CC ?
  descriptions : [a,b] # If given as a list, only those descriptions
    ↳ will be included, else all descriptions with this DSP-ID will be used
```

4.2. Name Spaces

Name spaces are key value pair of prefix and URI. YAMA follows XML specification for prefixes and URI. URI should be as recommended in RFC3986 (<https://tools.ietf.org/html/rfc3986>). during the document processing, YAMA can generate Qnames from this namespace key values.

Table 1: YAMA Metadata for the Application Profile

Key	Type	De-fault	Description	Sample	Required
id	Text	-	A unique ID for the Description Set	My-Book-CaseDS	R
title	Text	-	Title of the MAP	My Book Case	R
version	Text	-	Version following semver.org Semantic Versioning	X.Y.Z or X.Y or X	R
date	Text	-	Release date of AP. Any valid ISO-8601 string.	2018-12-29	
subject	Text	-	Subject or topic		
creator	Text		Person, URL or more contact information, Free text		Creator can be repeated if there are multiple creators
homepage					
pub- lisher					
keyword					
open	Boolean	true	Open or closed MAP, will be respected in Application Profile curation services.		
li- cense	Free Text	CC	License of the MAP		
de- scrip- tions	Ar- ray	[a,b]	If given as a list, only those descriptions will be included, else all descriptions with this MAP-ID will be used		

Table 2: YAMA Elements for Descriptions

KEY	TYPE	DEFAULT	DESCRIPTION	RE-QUIRED
label	Text	-	Label of the Element	
name	Text	Value from label	Human Friendly Name	R
min	Intiger	0		
max	Intiger	n		
standalone	Boolean	true		
X class			The class of a description	
description	Text		Short Description	
long_description	Text		Detailed Description	
statements	Array		[a,b] Statements belongs to this description	R

```
namespaces      :
  prefix_1        : uri_1
  prefix_2        : uri_2
```

4.3. Descriptions

Single resources are described under descriptions with a unique ID for each descriptions. Every unique descriptions ID can have multiple key value pairs to describe that resource. See table 2 for list of elements in YAMA description scheme.

```
descriptions    :
example_description_01:
  label          : # (R) Label of the Element
  name           : # Human Friendly Name
  min            :
  max            :
  standalone     : true   # Default, true
  X class        :
  X subclass     :
  description    : # Short Description
  long_description: # Detailed Description
  statements     : [a,b]  #
```

4.4. Statements

A statement is a single data element used to describe a resource that is defined as a description. The statement defines the possible values, and any other constraints. See table 3 for list of elements in YAMA statements.

```
statements      :
example_statement_01 :
  label          : # (R) Label of the Element
  name           : # Human Friendly Name
  min            :
  max            :
  type           :
  description    : # Short Description
  long_description: # Detailed Description
  constraint     : x or [x,y] # IDs of constraints
```

Table 3: YAMA elements for statements

KEY	TYPE	DEFAULT	DESCRIPTION	REQUIRED
label			[R] Label of the Element	
name			Human Friendly Name	
min				
max				
type				
description			Short Description	
long_description			Detailed Description	
constraint			x or [x,y] IDs of constraints	

Appendix B : Example YAMA Document

```

1 %YAML 1.2
2 ---
3 #%%YAMA 0.8
4 meta:
5   id: dcat-ap
6   title: DCAT Application Profile for Data Portals in Europe
7   version: 1.2.1
8   date: '2019-05-28'
9   subject: Application profile for data portals in Europe (DCAT-AP)
10  description: The DCAT Application profile for data portals in Europe (DCAT-AP)
    ↳ is
    ↳ a specification based on the Data Catalogue vocabulary (DCAT) for describing
    ↳ public
12  ↳ sector datasets in Europe. Its basic use case is to enable a cross-data
    ↳ portal
13  ↳ search for data sets and make public sector data better searchable across
    ↳ borders
14  ↳ and sectors. This can be achieved by the exchange of descriptions of data
    ↳ sets
15  ↳ among data portals.
16  license: ISA Open Metadata Licence v1.1
17  license-url: https://joinup.ec.europa.eu/licence/isa-open-metadata-licence-v11
18  creator: DCAT-AP Working Group
19  website: https://github.com/SEMICeu/DCAT-AP
20  logo:
    ↳ https://joinup.ec.europa.eu/sites/default/files/imagecache/community_logo/DCAT_application_p
21
22 namespaces:
23   adms: http://www.w3.org/ns/adms#
24   dcat: http://www.w3.org/ns/dcat#
25   dct: http://purl.org/dc/terms/
26   foaf: http://xmlns.com/foaf/0.1/
27   owl: http://www.w3.org/2002/07/owl#
28   rdfs: http://www.w3.org/2000/01/rdf-schema#
29   schema: http://schema.org/
30   skos: http://www.w3.org/2004/02/skos/core#
31   spdx: http://spdx.org/rdf/terms#
32   xsd: http://www.w3.org/2001/XMLSchema#
33   vcard: http://www.w3.org/2006/vcard/ns#
34

```

```

35 constraints:
36   voc_iana_media_types: &voc_iana_media_types
37     type: vocabulary
38     vocabulary_name: IANA Media Types
39     URI: http://www.iana.org/assignments/media-types/media-types.xhtml
40     notes: ''
41   voc_dataset_theme_vocabulary: &voc_dataset_theme_vocabulary
42     type: vocabulary
43     vocabulary_name: Dataset Theme Vocabulary
44     URI: http://publications.europa.eu/resource/dataset/data-theme
45     notes: The value to be used for this property is the URI of the vocabulary
        ↳ itself,
        i.e. the concept scheme, not the URIs of the concepts in the vocabulary.
46   voc_eu_vocabularies_frequency_named_authority_list:
47     ↳ &voc_eu_vocabularies_frequency_named_authority_list
48     type: vocabulary
49     vocabulary_name: EU Vocabularies Frequency Named Authority List
50     URI: http://publications.europa.eu/resource/authority/frequency
51     notes: ''
52   voc_eu_vocabularies_file_type_named_authority_list:
53     ↳ &voc_eu_vocabularies_file_type_named_authority_list
54     type: vocabulary
55     vocabulary_name: EU Vocabularies File Type Named Authority List
56     URI: http://publications.europa.eu/resource/authority/file-type
57     notes: ''
58   voc_eu_vocabularies_languages_named_authority_list:
59     ↳ &voc_eu_vocabularies_languages_named_authority_list
60     type: vocabulary
61     vocabulary_name: EU Vocabularies Languages Named Authority List
62     URI: http://publications.europa.eu/resource/authority/language
63     notes: ''
64   voc_eu_vocabularies_corporate_bodies_named_authority_list:
65     ↳ &voc_eu_vocabularies_corporate_bodies_named_authority_list
66     type: vocabulary
67     vocabulary_name: EU Vocabularies Corporate bodies Named Authority List
68     URI: http://publications.europa.eu/resource/authority/corporate-body
69     notes: The Corporate bodies NAL must be used for European institutions and a
        ↳ small
        set of international organisations. In case of other types of
        ↳ organisations,
        national, regional or local vocabularies should be used.
70   voc_geonames: &voc_geonames
71     type: vocabulary
72     vocabulary_name: Geonames
73     URI: http://sws.geonames.org/
74     notes: The EU Vocabularies Name Authority Lists must be used for continents,
        ↳ countries
        and places that are in those lists; if a particular location is not in one
        ↳ of
        the mentioned Named Authority Lists, Geonames URI must be used.
75   voc_eu_vocabularies_places_named_authority_list:
76     ↳ &voc_eu_vocabularies_places_named_authority_list
77     type: vocabulary
78     vocabulary_name: EU Vocabularies Places Named Authority List
79     URI: http://publications.europa.eu/resource/authority/place/

```

```

80    notes: The EU Vocabularies Name Authority Lists must be used for continents,
81        ↳ countries
82        and places that are in those lists; if a particular location is not in one
83            ↳ of
84            the mentioned Named Authority Lists, Geonames URIs must be used.
85    voc_eu_vocabularies_countries_named_authority_list:
86        ↳ &voc_eu_vocabularies_countries_named_authority_list
87        type: vocabulary
88        vocabulary_name: EU Vocabularies Countries Named Authority List
89        URI: http://publications.europa.eu/resource/authority/country
90    notes: The EU Vocabularies Name Authority Lists must be used for continents,
91        ↳ countries
92        and places that are in those lists; if a particular location is not in one
93            ↳ of
94            the mentioned Named Authority Lists, Geonames URIs must be used.
95    voc_eu_vocabularies_continents_named_authority_list:
96        ↳ &voc_eu_vocabularies_continents_named_authority_list
97        type: vocabulary
98        vocabulary_name: EU Vocabularies Continents Named Authority List
99        URI: http://publications.europa.eu/resource/authority/continent/
100    notes: The EU Vocabularies Name Authority Lists must be used for continents,
101        ↳ countries
102        and places that are in those lists; if a particular location is not in one
103            ↳ of
104            the mentioned Named Authority Lists, Geonames URIs must be used.
105    voc_adms_change_type_vocabulary: &voc_adms_change_type_vocabulary
106        type: vocabulary
107        vocabulary_name: ADMS change type vocabulary
108        URI: http://purl.org/adms/changetype/
109    notes: :created, :updated, :deleted
110    voc_adms_status_vocabulary: &voc_adms_status_vocabulary
111        type: vocabulary
112        vocabulary_name: ADMS status vocabulary
113        URI: http://purl.org/adms/status/
114    notes: The list of terms in the ADMS status vocabulary is included in the
115        ↳ ADMS
116            specification
117    voc_adms_publisher_type_vocabulary: &voc_adms_publisher_type_vocabulary
118        type: vocabulary
119        vocabulary_name: ADMS publisher type vocabulary
120        URI: http://purl.org/adms/publishertype/
121    notes: The list of terms in the ADMS publisher type vocabulary is included in
122        ↳ the
123            ADMS specification
124
125    statements:
126        pr_dataset: &pr_dataset
127            label: dataset
128            property: dcat:dataset
129            range: dcat:Dataset

```

```

126   description: This property links the Catalogue with a Dataset that is part of
127     the Catalogue.
128   min: 1
129   max: n
130   pr_description: &pr_description
131     label: description
132     property: dct:description
133     range: rdfs:Literal
134   description: This property contains a free-text account of the Distribution.
135     → This
136       property can be repeated for parallel language versions of the description.
137   min: 0
138   max: n
139   pr_publisher: &pr_publisher
140     label: publisher
141     property: dct:publisher
142     range: foaf:Agent
143   description: This property refers to an entity (organisation) responsible for
144     making the Dataset available.
145   min: 0
146   max: 1
147   constraints: *voc_eu_vocabularies_corporate_bodies_named_authority_list
148   pr_title: &pr_title
149     label: title
150     property: dct:title
151     range: rdfs:Literal
152   description: This property contains a name of the category scheme. May be
153     → repeated
154       for different versions of the name
155   min: 1
156   max: n
157   pr_homepage: &pr_homepage
158     label: homepage
159     property: foaf:homepage
160     range: foaf:Document
161   description: This property refers to a web page that acts as the main page
162     → for
163       the Catalogue.
164   min: 0
165   max: 1
166   pr_language: &pr_language
167     label: language
168     property: dct:language
169     range: dct:LinguisticSystem
170   description: This property refers to a language used in the Distribution.
171     → This
172       property can be repeated if the metadata is provided in multiple languages.
173   min: 0
174   max: n
175   constraints: *voc_eu_vocabularies_languages_named_authority_list
176   pr_licence: &pr_licence
177     label: licence
178     property: dct:license
179     range: dct:LicenseDocument
180   description: This property refers to the licence under which the Distribution
181     is made available.

```

```

178     min: 0
179     max: 1
180     pr_release_date: &pr_release_date
181         label: release date
182         property: dct:issued
183         range: rdfs:Literal
184         description: This property contains the date of formal issuance (e.g.,
185             → publication)
186             of the Distribution.
186     min: 0
187     max: 1
188     pr_themes: &pr_themes
189         label: themes
190         property: dcat:themeTaxonomy
191         range: skos:ConceptScheme
192         description: This property refers to a knowledge organization system used to
193             → classify
193             the Catalogue's Datasets.
194     min: 0
195     max: n
196     constraints: *voc_dataset_theme_vocabulary
197     pr_update_modification_date: &pr_update_modification_date
198         label: update/ modification date
199         property: dct:modified
200         range: rdfs:Literal
201         description: This property contains the most recent date on which the
202             → Distribution
202             was changed or modified.
203     min: 0
204     max: 1
205     pr_has_part: &pr_has_part
206         label: has part
207         property: dct:hasPart
208         range: dcat:Catalog
209         description: This property refers to a related Catalogue that is part of the
209             → described
210                 Catalogue
211     min: 0
212     max: n
213     pr_is_part_of: &pr_is_part_of
214         label: is part of
215         property: dct:isPartOf
216         range: dcat:Catalog
217         description: This property refers to a related Catalogue in which the
217             → described
218                 Catalogue is physically or logically included.
219     min: 0
220     max: 1
221     pr_record: &pr_record
222         label: record
223         property: dcat:record
224         range: dcat:CatalogRecord
225         description: This property refers to a Catalogue Record that is part of the
225             → Catalogue
226     min: 0
227     max: n

```

```

228 pr_rights: &pr_rights
229   label: rights
230   property: dct:rights
231   range: dct:RightsStatement
232   description: This property refers to a statement that specifies rights
233     ↪ associated
234       with the Distribution.
235   min: 0
236   max: 1
237 pr_spatial_geographic: &pr_spatial_geographic
238   label: spatial / geographic
239   property: dct:spatial
240   range: dct:Location
241   description: This property refers to a geographical area covered by the
242     ↪ Catalogue.
243   min: 0
244   max: n
245 pr_primary_topic: &pr_primary_topic
246   label: primary topic
247   property: foaf:primaryTopic
248   range: dcat:Dataset
249   description: This property links the Catalogue Record to the Dataset
250     ↪ described
251       in the record.
252   min: 1
253   max: 1
254 pr_application_profile: &pr_application_profile
255   label: application profile
256   property: dct:conformsTo
257   range: rdfs:Resource
258   description: This property refers to an Application Profile that the
259     ↪ Dataset's
260       metadata conforms to
261   min: 0
262   max: 1
263 pr_change_type: &pr_change_type
264   label: change type
265   property: adms:status
266   range: skos:Concept
267   description: This property refers to the type of the latest revision of a
268     ↪ Dataset's
269       entry in the Catalogue. It MUST take one of the values :created, :updated
270         ↪ or
271         :deleted depending on whether this latest revision is a result of a
272           ↪ creation,
273             update or deletion.
274   min: 0
275   max: 1
276 pr_listing_date: &pr_listing_date
277   label: listing date
278   property: dct:issued
279   range: rdfs:Literal
280   description: This property contains the date on which the description of the
281     ↪ Dataset
282       was included in the Catalogue.
283   min: 0

```

```

276     max: 1
277     pr_source_metadata: &pr_source_metadata
278         label: source metadata
279         property: dct:source
280         range: dcat:CatalogRecord
281         description: This property refers to the original metadata that was used in
282             ↳ creating
283                 metadata for the Dataset
284         min: 0
285         max: 1
286     pr_contact_point: &pr_contact_point
287         label: contact point
288         property: dcat:contactPoint
289         range: vcard:Kind
290         description: This property contains contact information that can be used for
291             ↳ sending
292                 comments about the Dataset.
293         min: 0
294         max: n
295     pr_dataset_distribution: &pr_dataset_distribution
296         label: dataset distribution
297         property: dcat:distribution
298         range: dcat:Distribution
299         description: This property links the Dataset to an available Distribution.
300         min: 0
301         max: n
302     pr_keyword_tag: &pr_keyword_tag
303         label: keyword/ tag
304         property: dcat:keyword
305         range: rdfs:Literal
306         description: This property contains a keyword or tag describing the Dataset.
307         min: 0
308         max: n
309     pr_theme_category: &pr_theme_category
310         label: theme/ category
311         property: dcat:theme
312         range: skos:Concept
313         description: This property refers to a category of the Dataset. A Dataset may
314             be associated with multiple themes.
315         min: 0
316         max: n
317         constraints: *voc_dataset_theme_vocabulary
318     pr_access_rights: &pr_access_rights
319         label: access rights
320         property: dct:accessRights
321         range: dct:RightsStatement
322         description: This property refers to information that indicates whether the
323             ↳ Dataset
324                 is open data, has access restrictions or is not public. A controlled
325                     ↳ vocabulary
326                     with three members (:public, :restricted, :non-public) will be created and
327                         ↳ maintained
328                     by the Publications Office of the EU.
329         min: 0
330         max: 1
331     pr_conforms_to: &pr_conforms_to

```

```

327     label: conforms to
328     property: dct:conformsTo
329     range: dct:Standard
330     description: This property refers to an implementing rule or other
331       ↳ specification.
332     min: 0
333     max: n
334   pr_documentation: &pr_documentation
335     label: documentation
336     property: foaf:page
337     range: foaf:Document
338     description: This property refers to a page or document about this
339       ↳ Distribution.
340     min: 0
341     max: n
342   pr_frequency: &pr_frequency
343     label: frequency
344     property: dct:accrualPeriodicity
345     range: dct:Frequency
346     description: This property refers to the frequency at which the Dataset is
347       ↳ updated.
348     min: 0
349     max: 1
350   constraints: *voc_eu_vocabularies_frequency_named_authority_list
351   pr_has_version: &pr_has_version
352     label: has version
353     property: dct:hasVersion
354     range: dcat:Dataset
355     description: This property refers to a related Dataset that is a version,
356       ↳ edition,
357       or adaptation of the described Dataset.
358     min: 0
359     max: n
360   pr_identifier: &pr_identifier
361     label: identifier
362     property: dct:identifier
363     range: rdfs:Literal
364     description: This property contains the main identifier for the Dataset, e.g.
365       the URI or other unique identifier in the context of the Catalogue.
366     min: 0
367     max: n
368   pr_is_version_of: &pr_is_version_of
369     label: is version of
370     property: dct:isVersionOf
371     range: dcat:Dataset
372     description: This property refers to a related Dataset of which the described
373       Dataset is a version, edition, or adaptation.
374     min: 0
375     max: n
376   pr_landing_page: &pr_landing_page
377     label: landing page
378     property: dcat:landingPage
379     range: foaf:Document
380     description: This property refers to a web page that provides access to the
381       ↳ Dataset,
382       its Distributions and/or additional information. It is intended to point to

```

```

378     a landing page at the original data provider, not to a page on a site of a
379     ↵   third
380     party, such as an aggregator.
381     min: 0
382     max: n
383     pr_other_identifier: &pr_other_identifier
384     label: other identifier
385     property: adms:identifier
386     range: adms:Identifier
387     description: This property refers to a secondary identifier of the Dataset,
388     ↵   such
389     as MAST/ADS[1], DataCite[2], DOI[3], EZID[4] or W3ID[5].
390     min: 0
391     max: n
392     pr_provenance: &pr_provenance
393     label: provenance
394     property: dct:provenance
395     range: dct:ProvenanceStatement
396     description: This property contains a statement about the lineage of a
397     ↵   Dataset.
398     min: 0
399     max: n
400     pr_related_resource: &pr_related_resource
401     label: related resource
402     property: dct:relation
403     range: rdfs:Resource
404     description: This property refers to a related resource.
405     min: 0
406     max: n
407     pr_sample: &pr_sample
408     label: sample
409     property: adms:sample
410     range: dcat:Distribution
411     description: This property refers to a sample distribution of the dataset
412     min: 0
413     max: n
414     pr_source: &pr_source
415     label: source
416     property: dct:source
417     range: dcat:Dataset
418     description: This property refers to a related Dataset from which the
419     ↵   described
420     Dataset is derived.
421     min: 0
422     max: n
423     pr_spatial_geographical_coverage: &pr_spatial_geographical_coverage
424     label: spatial/ geographical coverage
425     property: dct:spatial
426     range: dct:Location
427     description: This property refers to a geographic region that is covered by
428     ↵   the
        Dataset.
     min: 0
     max: n
     constraints:
       << : *voc_eu_vocabularies_continents_named_authority_list

```

```

429     URI: hdhakjsdkjhas
430     pr_temporal_coverage: &pr_temporal_coverage
431         label: temporal coverage
432         property: dct:temporal
433         range: dct:PeriodOfTime
434         description: This property refers to a temporal period that the Dataset
435             ↪ covers.
436         min: 0
437         max: n
438     pr_type: &pr_type
439         label: type
440         property: dct:type
441         range: skos:Concept
442         description: This property refers to a type of the agent that makes the
443             ↪ Catalogue
444             or Dataset available
445         min: 0
446         max: 1
447     pr_version: &pr_version
448         label: version
449         property: owl:versionInfo
450         range: rdfs:Literal
451         description: This property contains a version number or other version
452             ↪ designation
453             of the Dataset.
454         min: 0
455         max: 1
456     pr_version_notes: &pr_version_notes
457         label: version notes
458         property: adms:versionNotes
459         range: rdfs:Literal
460         description: This property contains a description of the differences between
461             ↪ this
462             version and a previous version of the Dataset. This property can be
463                 ↪ repeated
464                 for parallel language versions of the version notes.
465         min: 0
466         max: n
467     pr_access_url: &pr_access_url
468         label: access URL
469         property: dcat:accessURL
470         range: rdfs:Resource
471         description: This property contains a URL that gives access to a Distribution
472             of the Dataset. The resource at the access URL may contain information
473                 ↪ about
474                 how to get the Dataset.
475         min: 1
476         max: n
477     pr_format: &pr_format
478         label: format
479         property: dct:format
480         range: dct:MediaTypeOrExtent
481         description: This property refers to the file format of the Distribution.
482         min: 0
483         max: 1
484         constraints: *voc_eu_vocabularies_file_type_named_authority_list

```

```

479 pr_byte_size: &pr_byte_size
480   label: byte size
481   property: dcat:byteSize
482   range: rdfs:Literal
483   description: This property contains the size of a Distribution in bytes.
484   min: 0
485   max: 1
486 pr_checksum: &pr_checksum
487   label: checksum
488   property: spdx:checksum
489   range: spdx:Checksum
490   description: This property provides a mechanism that can be used to verify
491     ↳ that
492       the contents of a distribution have not changed
493   min: 0
494   max: 1
495 pr_download_url: &pr_download_url
496   label: download URL
497   property: dcat:downloadURL
498   range: rdfs:Resource
499   description: This property contains a URL that is a direct link to a
500     ↳ downloadable
501       file in a given format.
502   min: 0
503   max: n
504 pr_linked_schemas: &pr_linked_schemas
505   label: linked schemas
506   property: dct:conformsTo
507   range: dct:Standard
508   description: This property refers to an established schema to which the
509     ↳ described
510       Distribution conforms.
511   min: 0
512   max: n
513 pr_media_type: &pr_media_type
514   label: media type
515   property: dcat:mediaType
516   range: dct:MediaTypeOrExtent
517   description: This property refers to the media type of the Distribution as
518     ↳ defined
519       in the official register of media types managed by IANA.
520   min: 0
521   max: 1
522   constraints: *voc_iana_media_types
523 pr_status: &pr_status
524   label: status
525   property: adms:status
526   range: skos:Concept
527   description: This property refers to the maturity of the Distribution
528   min: 0
529   max: 1
530   constraints: *voc_adms_status_vocabulary
531 pr_name: &pr_name
532   label: name
533   property: foaf:name
534   range: rdfs:Literal

```

```

531     description: This property contains a name of the agent. This property can be
532         repeated for different versions of the name (e.g. the name in different
533             → languages)
534     min: 1
535     max: n
536     pr_preferred_label: &pr_preferred_label
537         label: preferred label
538         property: skos:prefLabel
539         range: rdfs:Literal
540         description: This property contains a preferred label of the category. This
541             → property
542                 can be repeated for parallel language versions of the label.
543     min: 1
544     max: n
545     pr_algorithm: &pr_algorithm
546         label: algorithm
547         property: spdx:algorithm
548         range: spdx:checksumAlgorithm_sha1
549         description: This property identifies the algorithm used to produce the
550             → subject
551                 Checksum. Currently, SHA-1 is the only supported algorithm. It is
552                     → anticipated
553                         that other algorithms will be supported at a later time.
554     min: 1
555     max: 1
556     pr_checksum_value: &pr_checksum_value
557         label: checksum value
558         property: spdx:checksumValue
559         range: rdfs:Literal
560         description: This property provides a lower case hexadecimal encoded digest
561             → value
562                 produced using a specific algorithm.
563     min: 1
564     max: 1
565     pr_notation: &pr_notation
566         label: notation
567         property: skos:notation
568         range: rdfs:Literal
569         description: This property contains a string that is an identifier in the
570             → context
571                 of the identifier scheme referenced by its datatype.
572     min: 0
573     max: 1
574     pr_licence_type: &pr_licence_type
575         label: licence type
576         property: dct:type
577         range: skos:Concept
578         description: This property refers to a type of licence, e.g. indicating
579             → 'public'
580                 'domain' or 'royalties required'.
581     min: 0
582     max: n
583     constraints: *voc_adms_licence_type_vocabulary
584     pr_start_date_time: &pr_start_date_time
585         label: start date/time
586         property: schema:startDate

```

```

580     range: rdfs:Literal
581     description: This property contains the start of the period
582     min: 0
583     max: 1
584     pr_end_date_time: &pr_end_date_time
585     label: end date/time
586     property: schema:endDate
587     range: rdfs:Literal
588     description: This property contains the end of the period
589     min: 0
590     max: 1
591
592 classes:
593   cl_agent: &cl_agent
594     label: Agent
595     property: foaf:Agent
596     requirement: mandatory
597     reference: http://xmlns.com/foaf/spec/#term_Agent
598       ↳ http://www.w3.org/TR/vocab-org/
599     notes: An entity that is associated with Catalogues and/or Datasets. If the
      ↳ Agent
      is an organisation, the use of the Organization Ontology is recommended.
      ↳ See
600     section 7 for a discussion on Agent roles.
601 mandatory_properties:
602   - *pr_name
603 recommended_properties:
604   - *pr_licence_type
605 cl_catalogue: &cl_catalogue
606   label: Catalogue
607   property: dcat:Catalog
608   requirement: mandatory
609   reference: http://www.w3.org/TR/2013/WD-vocab-dcat-20130312/#class-catalog
610   notes: A catalogue or repository that hosts the Datasets being described.
611 mandatory_properties:
612   - *pr_dataset
613   - *pr_description
614   - *pr_publisher
615   - *pr_title
616 recommended_properties:
617   - *pr_homepage
618   - *pr_language
619   - *pr_licence
620   - *pr_listing_date
621   - *pr_themes
622   - *pr_update_modification_date
623 optional_properties:
624   - *pr_has_part
625   - *pr_is_part_of
626   - *pr_record
627   - *pr_rights
628   - *pr_spatial_geographical_coverage
629 cl_dataset: &cl_dataset
630   label: Dataset
631   property: dcat:Dataset
632   requirement: mandatory

```

```

633 reference: http://www.w3.org/TR/2013/WD-vocab-dcat-20130312/#class-dataset
634 notes: A conceptual entity that represents the information published.
635 mandatory_properties:
636   - *pr_description
637   - *pr_title
638 recommended_properties:
639   - *pr_contact_point
640   - *pr_dataset_distribution
641   - *pr_keyword_tag
642   - *pr_publisher
643   - *pr_theme_category
644 optional_properties:
645   - *pr_other_identifier
646   - *pr_sample
647   - *pr_version_notes
648   - *pr_landing_page
649   - *pr_access_rights
650   - *pr_frequency
651   - *pr_linked_schemas
652   - *pr_has_version
653   - *pr_is_version_of
654   - *pr_identifier
655   - *pr_listing_date
656   - *pr_language
657   - *pr_update_modification_date
658   - *pr_provenance
659   - *pr_related_resource
660   - *pr_source
661   - *pr_spatial_geographical_coverage
662   - *pr_temporal_coverage
663   - *pr_licence_type
664   - *pr_documentation
665   - *pr_version
666 cl_literal: &ccl_literal
667   label: Literal
668   property: rdfs:Literal
669   requirement: mandatory
670   reference: http://www.w3.org/TR/rdf-concepts/#section-Literals
671   notes: A literal value such as a string or integer; Literals may be typed,
672     ↳ e.g.
673     ↳ as a date according to xsd:date. Literals that contain human-readable text
674       ↳ have
675       ↳ an optional language tag as defined by BCP 47 .
676 cl_resource: &ccl_resource
677   label: Resource
678   property: rdfs:Resource
679   requirement: mandatory
680   reference: http://www.w3.org/TR/rdf-schema/#ch_resource
681   notes: Anything described by RDF.
682 cl_category: &ccl_category
683   label: Category
684   property: skos:Concept
685   requirement: recommended
686   reference:
687     ↳ http://www.w3.org/TR/2013/WD-vocab-dcat-20130312/#class-category-and-category-scheme
688   notes: A subject of a Dataset.

```

```

686     mandatory_properties:
687         - *pr_preferred_label
688     cl_category_scheme: &cl_category_scheme
689         label: Category scheme
690         property: skos:ConceptScheme
691         requirement: recommended
692         reference:
693             ↳ http://www.w3.org/TR/2013/WD-vocab-dcat-20130312/#class-category-and-category-scheme
694     notes: A concept collection (e.g. controlled vocabulary) in which the
695         ↳ Category
696         is defined.
697     mandatory_properties:
698         - *pr_title
699     cl_distribution: &cl_distribution
700         label: Distribution
701         property: dcat:Distribution
702         requirement: recommended
703         reference:
704             ↳ http://www.w3.org/TR/2013/WD-vocab-dcat-20130312/#class-distribution
705     notes: A physical embodiment of the Dataset in a particular format.
706     mandatory_properties:
707         - *pr_access_url
708     recommended_properties:
709         - *pr_description
710         - *pr_format
711         - *pr_licence
712     optional_properties:
713         - *pr_status
714         - *pr_byte_size
715         - *pr_download_url
716         - *pr_media_type
717         - *pr_linked_schemas
718         - *pr_listing_date
719         - *pr_language
720         - *pr_update_modification_date
721         - *pr_rights
722         - *pr_title
723         - *pr_documentation
724         - *pr_checksum
725     cl_licence_document: &cl_licence_document
726         label: Licence document
727         property: dct:LicenseDocument
728         requirement: recommended
729         reference:
730             ↳ http://dublincore.org/documents/2012/06/14/dcmi-terms/?v=terms#LicenseDocument
731     notes: A legal document giving official permission to do something with a
732         ↳ resource.
733     recommended_properties:
734         - *pr_licence_type
735     cl_catalogue_record: &cl_catalogue_record
736         label: Catalogue Record
737         property: dcat:CatalogRecord
738         requirement: optional
739         reference:
740             ↳ http://www.w3.org/TR/2013/WD-vocab-dcat-20130312/#class-catalog-record
741     notes: A description of a Dataset's entry in the Catalogue.

```

```

736     mandatory_properties:
737         - *pr_update_modification_date
738         - *pr_primary_topic
739     recommended_properties:
740         - *pr_linked_schemas
741         - *pr_status
742         - *pr_listing_date
743     optional_properties:
744         - *pr_description
745         - *pr_language
746         - *pr_source
747         - *pr_title
748 cl_checksum: &ccl_checksum
749     label: Checksum
750     property: spdx:Checksum
751     requirement: optional
752     reference: http://spdx.org/rdf/terms#Checksum
753     notes: A value that allows the contents of a file to be authenticated. This
754         ↪ class
755         allows the results of a variety of checksum and cryptographic message
756             ↪ digest
757             algorithms to be represented.
758     mandatory_properties:
759         - *pr_algorithm
760         - *pr_checksum_value
761 cl_document: &ccl_document
762     label: Document
763     property: foaf:Document
764     requirement: optional
765     reference: http://xmlns.com/foaf/spec/#term_Document
766     notes: A textual resource intended for human consumption that contains
767         ↪ information,
768             e.g. a web page about a Dataset.
769 cl_frequency: &ccl_frequency
770     label: Frequency
771     property: dct:Frequency
772     requirement: optional
773     reference: http://dublincore.org/documents/dc/terms/#terms-Frequency
774     notes: A rate at which something recurs, e.g. the publication of a Dataset.
775 cl_identifier: &ccl_identifier
776     label: Identifier
777     property: adms:Identifier
778     requirement: optional
779     reference: http://www.w3.org/TR/vocab-adms/#identifier
780     notes: An identifier in a particular context, consisting of the string that
781         ↪ is
782         the identifier; an optional identifier for the identifier scheme; an
783             ↪ optional
784             identifier for the version of the identifier scheme; an optional identifier
785                 for the agency that manages the identifier scheme
786     mandatory_properties:
787         - *pr_notation
788 cl_kind: &ccl_kind
789     label: Kind
790     property: vcard:Kind
791     requirement: optional

```

```

787 reference: http://www.w3.org/TR/2014/NOTE-vcard-rdf-20140522/#d4e181
788 notes: A description following the vCard specification, e.g. to provide
    ↳ telephone
789     number and e-mail address for a contact point. Note that the class Kind is
    ↳ the
790     parent class for the four explicit types of vCards (Individual,
    ↳ Organization,
    Location, Group).
791 cl_linguistic_system: &cl_linguistic_system
792     label: Linguistic system
793     property: dct:LinguisticSystem
794     requirement: optional
795     reference: http://dublincore.org/documents/dcmi-terms/#terms-LinguisticSystem
796     notes: A system of signs, symbols, sounds, gestures, or rules used in
    ↳ communication,
    e.g. a language
797 cl_location: &cl_location
798     label: Location
799     property: dct:Location
800     requirement: optional
801     reference: http://dublincore.org/documents/dcmi-terms/#terms-Location
802     notes: A spatial region or named place. It can be represented using a
    ↳ controlled
803         vocabulary or with geographic coordinates. In the latter case, the use of
    ↳ the
804         Core Location Vocabulary is recommended, following the approach described
    ↳ in
805         the GeoDCAT-AP specification.
806 cl_media_type_or_extent: &cl_media_type_or_extent
807     label: Media type or extent
808     property: dct:MediaTypeOrExtent
809     requirement: optional
810     reference:
    ↳ http://dublincore.org/documents/dcmi-terms/#terms-MediaTypeOrExtent
811     notes: A media type or extent, e.g. the format of a computer file
812 cl_period_of_time: &cl_period_of_time
813     label: Period of time
814     property: dct:PeriodOfTime
815     requirement: optional
816     reference: http://dublincore.org/documents/dcmi-terms/#terms-PeriodOfTime
817     notes: An interval of time that is named or defined by its start and end
    ↳ dates.
818     optional_properties:
819         - *pr_start_date_time
820         - *pr_end_date_time
821 cl_publisher_type: &cl_publisher_type
822     label: Publisher type
823     property: skos:Concept
824     requirement: optional
825     reference: http://www.w3.org/TR/vocab-adms/#dcterms-type
826     notes: A type of organisation that acts as a publisher
827 cl_rights_statement: &cl_rights_statement
828     label: Rights statement
829     property: dct:RightsStatement
830     requirement: optional
831     reference: http://dublincore.org/documents/dcmi-terms/#terms-RightsStatement

```

```

834 notes: A statement about the intellectual property rights (IPR) held in or
835   ↵ over
836   a resource, a legal document giving official permission to do something
837     ↵ with
838   a resource, or a statement about access rights.
839 cl_standard: &cl_standard
840   label: Standard
841   property: dct:Standard
842   requirement: optional
843   reference: http://dublincore.org/documents/dcmi-terms/#terms-Standard
844   notes: A standard or other specification to which a Dataset or Distribution
845     ↵ conforms
846 cl_status: &cl_status
847   label: Status
848   property: skos:Concept
849   requirement: optional
850   reference: http://www.w3.org/TR/vocab-adms/#status
851   notes: An indication of the maturity of a Distribution or the type of change
852     ↵ of
853     a Catalogue Record.
854 cl_provenance_statement: &cl_provenance_statement
855   label: Provenance Statement
856   property: dct:ProvenanceStatement
857   requirement: optional
858   reference:
859     ↵ http://dublincore.org/documents/dcmi-terms/#terms-ProvenanceStatement
860   notes: A statement of any changes in ownership and custody of a resource
861     ↵ since
862     its creation that are significant for its authenticity, integrity, and
863       ↵ interpretation

```