

# List of Figures

2.1	Phase diagram for <sup>4</sup> helium . . . . .	7
2.2	Temperature dependence of $\frac{\rho_l}{\rho}$ and $\frac{\rho_s}{\rho}$ at the saturated vapor pressure. . . . .	9
2.3	Dependence of first-sound velocity on temperature and pressure. . . . .	15
2.4	Dependence of second-sound velocity on temperature and pressure. . . . .	16
2.5	Thermal expansion coefficient of liquid helium at saturated vapor pressure. . . . .	18
2.6	Variation of the coefficient $\frac{T}{2} \frac{\partial}{\partial T} \ln \left( a_{II}^3 \frac{\partial s}{\partial T} \right)$ with temperature at saturated vapor and other four pressures. . . . .	21
2.7	One-dimensional steady flow for shock wave. . . . .	23
2.8	One-dimensional steady flow in shock tube. . . . .	28
3.1	Schematic illustration of interpolation for thermodynamic quantity. . . . .	36
4.1	The schematic illustration of the superfluid shock tube facility.	39
4.2	The photograph of the superfluid shock tube facility. . . . .	39
4.3	The structure of the high-pressure driver section. . . . .	41
4.4	The schematic illustration of the low-pressure tube section. . . . .	42
4.5	The photograph of cryogenic shock tube section. . . . .	43
4.6	The detail structure of the test section. . . . .	44
4.7	The photograph of the test section. . . . .	45
4.8	The cross-sectional view of cryostat section. . . . .	47
4.9	The photograph of the cryostats section. . . . .	48
4.10	Evacuation and automatic operation system. . . . .	50
4.11	Schematic diagram of the sequence of automatic operation. . . . .	51

4.12	The schematic illustration of propagating shock waves in the cryogenic shock tube. . . . .	53
4.13	The photograph of the piezo-electric pressure transducer1. . . . .	55
4.14	The photograph of the piezo-electric pressure transducer2. . . . .	55
4.15	Schematic illustration of the resistivity variations with temperature of <i>Type I</i> and <i>Type II</i> superconductor. . . . .	56
4.16	Schematic illustration of superconductive temperature sensor. . . . .	58
4.17	The photograph of superconductive temperature sensor. . . . .	58
4.18	Schematic illustration of the principle of Schlieren visualization method. . . . .	60
4.19	The arrangement of Schlieren optics. . . . .	62
5.1	Pressure history of typical shock wave. (driver gas; helium, driven gas; nitrogen), $p_1 = 53.50 \text{ kPa}$ , Both gases at $293 \text{ K}$ . . . . .	66
5.2	Pressure history of typical shock wave. (driver gas; helium, driven gas; nitrogen), $p_1 = 1.50 \text{ kPa}$ , Both gases at $293 \text{ K}$ . . . . .	66
5.3	Pressure history in the case of saturated nitrogen vapor $77 \text{ K}$ in the low-pressure tube section. (driver gas; helium, driven gas; nitrogen), $p_1 = 19.50 \text{ kPa}$ . . . . .	67
5.4	Pressure history in the case of helium gas. (driver gas; helium, driven gas; helium), $p_1 = 53.5 \text{ kPa}$ , Both gases at $293 \text{ K}$ . . . . .	68
5.5	Pressure history in the case of helium gas. (driver gas; helium, driven gas; helium), $p_1 = 2.66 \text{ kPa}$ , Both gases at $293 \text{ K}$ . . . . .	68
5.6	Pressure history in the case of saturated helium vapor at $2 \text{ K}$ in the low-pressure tube section. (driver gas; helium, driven gas; helium), $p_1 = 2.06 \text{ kPa}$ . . . . .	69
5.7	Shock wave performance of superfluid shock tube facility. $p_{41}$ vs. $M_{SV}$ . . . . .	70
5.8	Shock wave performance of superfluid shock tube facility. $p_{41}$ vs. pressure jump $p_{21}$ . . . . .	70
5.9	Shock wave performance of superfluid shock tube facility. $p_{41}$ vs. $M_{SL}$ . . . . .	71

5.10	Shock wave performance of superfluid shock tube facility. $p_{41}$ vs. $\Delta p$ in <i>HeII</i> . . . . .	71
5.11	Impinging shock wave condition in the helium vapor. $p_{21}$ vs. $M_{SV}$ . . . . .	72
5.12	Typical example of time variation of detected signals. . . . .	74
5.13	Pressure variations associated with the propagating shock waves. . . . .	76
5.14	$U_{RL}/U_{SL}$ versus Transmitted shock Mach number $M_{SL}$ . . . . .	79
5.15	Dependence of first-sound velocity on temperature and pressure. . . . .	79
5.16	Pressure jump $\Delta p$ result at the wave front of the transmitted compression shock wave in <i>HeII</i> as a function of shock Mach number $M_{SL}$ . . . . .	80
5.17	Variation of the temperature jump $\Delta T$ at the wave front of the transmitted compression shock wave with the shock Mach number $M_{SL}$ . . . . .	81
5.18	Visualization photograph of propagating transmitted compression shock wave in <i>HeII</i> . . . . .	83
5.19	Time variations of intensity of laser beam transmission and visualization photographs of transmitted compression shock wave . . . . .	85
5.20	Thermodynamic state near <i>HeII</i> free surface. . . . .	86
5.21	Thermodynamic state near liquid nitrogen free surface. . . . .	86
5.22	Pressure jump $\Delta p/p_1$ vs. shock Mach number $M_{SL}$ . . . . .	88
5.23	Temperature jump $\Delta T/T_1$ vs. shock Mach number $M_{SL}$ . . . . .	89
5.24	Shock adiabatic. . . . .	90
5.25	Hugoniot. . . . .	91
5.26	Normalized flow velocity $v/a^*$ behind a compression shock wave vs. shock Mach number $M_{SL}$ . . . . .	91
5.27	Normalized counterflow velocity $w/a^*$ behind a compression shock wave vs. shock Mach number $M_{SL}$ . . . . .	92
5.28	Flow velocity $v$ behind a compression shock wave vs. shock Mach number $M_{SL}$ . . . . .	92
5.29	Counterflow velocity $w$ behind a compression shock wave vs. shock Mach number $M_{SL}$ . . . . .	93

5.30	Entropy jump $\Delta s/s_1$ vs. shock Mach number $M_{SL}$ . . . . .	95
5.31	Entropy flux jump $\Delta \dot{s}/s_1$ vs. shock Mach number $M_{SL}$ . . . . .	95
5.32	The transient record of the temperature variation $\Delta T$ detected by the superconductive temperature sensor in <i>HeII</i> . . . . .	98
5.33	Temperature variation caused by stepwise heating in <i>HeII</i> . . . . .	99
5.34	Schematic illustration of appearance of limiting profile. . . . .	100
5.35	The amplitude of thermal shock wave $\Delta T$ as a function of pressure jump of transmitted compression shock wave $\Delta p_L$ . . . . .	101
5.36	Time variations of the temperature resulting from compression shock waves and a thermal shock wave measured at five locations. . . . .	103
5.37	Thermal boundary layer induced by impingement of a compression shock wave on <i>HeII</i> free surface. . . . .	104
5.38	Schematic illustration of various methods due to phase transitions. . . . .	105
5.39	Transient record of the <i>HeII</i> compression results without $\lambda$ -phase transition. . . . .	107
5.40	Transient record of the $\lambda$ -transition from <i>HeII</i> to <i>HeI</i> induced by shock compression. . . . .	108
5.41	A special case with $\lambda$ -transition; from <i>HeII</i> to <i>HeI</i> , resulting from shock compression by reflected compression shock wave from the shock tube bottom. . . . .	108
5.42	Thermal expansion coefficient of liquid helium, $\alpha$ , along saturated vapor pressure. . . . .	109
5.43	Visualization photographs of propagating thermal shock wave and <i>HeII-HeI</i> $\lambda$ -transition. . . . .	110
5.44	The temperature and pressure at the wave front of compression shock wave in <i>HeII</i> plotted for four initial temperatures of <i>HeII</i> . . . . .	111

## List of Author's Paper

1. Nagai, N., Takano, N., Yang, H.S., and Murakami, Study of two modes of shock waves and  $\lambda$ -transition in *HeII* induced by shock compression, Proceedings of the 22th International Symposium on Shock Wave., Shock Waves@London (2000)
2. Nagai, N., Takano, N., Yang, H.S., and Murakami, Study of shock waves and phase transition in *HeII* by using superfluid shock tube facility, *Advances in Cryogenic Engineering* **44** (2000)
3. Nagai, N., Yang, H.S., Takano, N., and Murakami, M. , Investigation of Two Modes of Shock Wave in *HeII* by Using Newly developed Superfluid Shock Tube Facility. *Proceedings of Seventeenth International Cryogenic Engineering Conference* 843-846 (1998)
4. Nagai, N., Yang, H.S., Takano, N., Murakami, M. and Teraoka, S., Development of Superfluid Shock Tube Facility. *Advances in Cryogenic Engineering* **43**1393-1400(1998)
5. Nagai, N., Yang, H.S., Takano, N., and Murakami, M., Development and Performance Test Results of Superfluid Shock-tube Facility. *Journal of Cryogenic Society of Japan* **33**(6) 403-409(1998)
6. Yang, H.S., Nagai, N., Takano, N., and Murakami, M., Experimental investigation of thermal shock wave induced by gas dynamic shock wave impingement, *Advances in Cryogenic Engineering* **44** (2000)
7. Takano, N., Nagai, N., Yang, H.S. and Murakami, M., Visualization study of phase transitions of *HeII* induced by shock wave compression, *Proceedings of 17th International Cryogenic Engineering Conference* 691-694 (1998)

8. Furukawa, T., Murakami, M., Nagai, H. and Iida, T., Transient evaporation phenomena in a pure vapour-liquid system, *Proceedings of the 5th International Heat Pipe Symposium* 255-260 (1996)
9. Iida, T., Murakami, M., Shimazaki, T. and Nagai, H., Visualization study of highly transient thermo-fluid dynamic phenomena in *HeII*, *Advances in Cryogenic Engineering* 41 249-256 (1996)
10. Iida, T., Murakami, M., Shimazaki, T. and Nagai, H., Visualization study on the thermo-hydrodynamic phenomena induced by pulsative heating in *HeII* by the use of a laser holographic interferometer, *Journal of Cryogenics* 36 934-949 (1996 )