

## List of Figures

2.1	B-ISDN architecture . . . . .	7
2.2	B-ISDN reference configuration . . . . .	8
2.3	Examples of physical configurations . . . . .	9
2.4	Examples of multiple interface arrangements . . . . .	10
2.5	B-ISDN user-network interface . . . . .	11
2.6	STM principle . . . . .	12
2.7	ATM principle and cell format . . . . .	13
2.8	Multimedia communication over ATM . . . . .	14
2.9	Processing delay versus cell size . . . . .	14
2.10	B-ISDN protocol reference model . . . . .	15
2.11	Service access point . . . . .	19
2.12	SONET system hierarchy . . . . .	22
2.13	SONET/SDH frame formats . . . . .	23
2.14	SONET STS-1 overhead octets . . . . .	25
2.15	Example of demultiplex and remultiplex . . . . .	25
2.16	Representative location of SPE in STS-1 Frame . . . . .	26
2.17	STS-1 pointer adjustment: negative pointer adjustment . . . . .	27
2.18	STS-1 pointer adjustment: positive pointer adjustment . . . . .	27
2.19	The cell based interface . . . . .	28
2.20	The frame structure at 34.368 Mbit/s . . . . .	30
2.21	The DS3 PLCP frame . . . . .	31

---

2.22	Cell rate decoupling . . . . .	32
2.23	HEC receiver actions . . . . .	33
2.24	Impact of random bit errors on HEC performance . . . . .	34
2.25	Cell delineation state diagram . . . . .	35
2.26	Impact of $\alpha$ on performance of cell delineation . . . . .	36
2.27	Impact of $\delta$ on performance of cell delineation . . . . .	36
2.28	ATM connection relationships . . . . .	37
2.29	ATM transport hierarchy . . . . .	38
2.30	Virtual path switching . . . . .	41
2.31	Virtual channel/virtual path switching . . . . .	42
2.32	ATM cell format . . . . .	44
2.33	Generic AAL protocol sublayer model . . . . .	51
2.34	SAR structure for AAL type 1 . . . . .	55
2.35	Examples of different AAL 1 data transfer mode . . . . .	56
2.36	AAL type 2 . . . . .	57
2.37	Message mode service . . . . .	58
2.38	Streaming mode service . . . . .	59
2.39	SAR structure for AAL 3/4 . . . . .	59
2.40	CPCS-PDU format for AAL type 3/4 . . . . .	61
2.41	Multiplexing example using AAL 3/4 . . . . .	62
2.42	CPCS-PDU format for AAL type 5 . . . . .	64
2.43	Multiplexing example using AAL 5 . . . . .	65
3.1	TCP/IP over ATM architecture . . . . .	68
3.2	TCP window behavior of slow start and congestion avoidance . . . . .	70
3.3	Behavior of fast retransmission and recovery . . . . .	72
3.4	Credit-based flow control . . . . .	73
3.5	Simple introduction of a close-loop control of ABR . . . . .	74

---

3.6	Enforcement of the EFCI . . . . .	76
3.7	Resource management cell fields . . . . .	77
3.8	TCP packet fragmentation over ATM . . . . .	86
3.9	Partial packet discard scheme . . . . .	87
3.10	Early packet discard scheme . . . . .	88
3.11	Buffer threshold . . . . .	89
4.1	Introduction of preliminary PDPD scheme. . . . .	91
4.2	Simulation model of preliminary PDPD. . . . .	92
4.3	Total throughput of TCP sources: RP size of two packets. . . . .	93
4.4	Normalized throughput of TCP sources: RP size of two packets. . . . .	93
4.5	Snapshots of buffer occupation in the switch when the buffer size is 1000 cells and the RP size is two packets. . . . .	95
4.6	Snapshots of buffer occupation in the switch when the buffer size is 2000 cells and the RP size is two packets. . . . .	96
4.7	Snapshots of buffer occupation in the switch when the buffer size is 3000 cells and the RP size is two packets. . . . .	97
4.8	Total throughput of TCP sources: RP size of three packets. . . . .	98
4.9	Normalized throughput of TCP sources: RP size of three packets. . . . .	99
4.10	Snapshots of buffer occupation in the switch when the buffer size is 1000 cells and the RP size is three packets. . . . .	100
4.11	Snapshots of buffer occupation in the switch when the buffer size is 2000 cells and the RP size is three packets. . . . .	101
4.12	Snapshots of buffer occupation in the switch when the buffer size is 2000 cells and the RP size is three packets. . . . .	102
4.13	Retransmission ratio. . . . .	103
4.14	Generalization of packet discard schemes. . . . .	104
4.15	Probabilistic Delayed Packet Discard scheme. . . . .	105

---

4.16 Simulation model of Probabilistic Delayed Packet Discard scheme. . . . .	106
4.17 Total throughput of TCP sources when RP size is two packets. . . . .	107
4.18 Normalized throughput when RP size is two packets. . . . .	108
4.19 Snapshots of buffer occupation in the switch when the probability $p$ is 0 (i.e., PPD).109	
4.20 Snapshots of buffer occupation in the switch when the probability $p$ is 0.25. . . .	110
4.21 Snapshots of buffer occupation in the switch when the probability $p$ is 0.5. . . .	111
4.22 Snapshots of buffer occupation in the switch when the probability $p$ is 0.75. . . .	112
4.23 Snapshots of buffer occupation in the switch when the probability $p$ is 1.0 (i.e., EPD). . . . .	113
4.24 Retransmission ratio when RP is two packets. . . . .	114
4.25 Total throughput of TCP sources when RP size is three packets. . . . .	115
4.26 Normalized throughput when RP size is three packets. . . . .	116
4.27 Snapshots of buffer occupation in switch when the probability $p$ is 0 (i.e., PPD). 117	
4.28 Snapshots of buffer occupation in the switch when the probability $p$ is 0.25. . . .	118
4.29 Snapshots of buffer occupation in the switch when the probability $p$ is 0.5. . . .	119
4.30 Snapshots of buffer occupation in the switch when the probability $p$ is 0.75. . . .	120
4.31 Snapshots of buffer occupation in the switch when the probability $p$ is 1.0 (i.e., EPD). . . . .	121
4.32 Retransmission ratio when RP is three packets. . . . .	122
4.33 Simulation model of multistage switches. . . . .	123
4.34 Throughput and normalized throughput with PDPD when $n$ is five. . . . .	124
4.35 Throughput and normalized throughput with PDPD when $n$ is ten. . . . .	125
4.36 Throughput and normalized throughput with PDPD when $n$ is five and the dis- tance is long. . . . .	127
4.37 Throughput and normalized throughput with PDPD when $n$ is ten and the dis- tance is long. . . . .	128

---

## List of Tables

2.1	Principles of B-ISDN . . . . .	5
2.2	The functions of B-ISDN in relation to the B-ISDN protocol reference model . .	17
2.3	SONET/SDH signal hierarchy . . . . .	21
2.4	STS-1 overhead bits . . . . .	24
2.5	Pre-assigned values of the cell header at the physical layer . . . . .	28
2.6	Header pattern for unassigned cell and idle cell identification . . . . .	32
2.7	Payload type indicator (PTI) field coding . . . . .	45
2.8	Pre-assigned cell header values at the UNI . . . . .	47
2.9	Pre-assigned values of the cell header at the ATM layer by the ATM Forum . . .	48
2.10	Summary of service categories and their features . . . . .	50
2.11	Service classification for AAL . . . . .	52
2.12	Relation of applications and the QoS parameters . . . . .	67
3.1	Parameter descriptions . . . . .	80
4.1	The comparison of average queue lengths when RP size is two packets. . . . .	108
4.2	The percentile average queue lengths when RP size is three packets. . . . .	116